
	Document Transmittal Sheet		RAPID KEYSTONE														
Title:	Roof and Rear Extension		CONSTRUCTION CONSULTANCY LTD														
Project N°:	201554		WWW	rkc	cltd cltd	CO II	IUN C k	UNS	ULIA	ANLY	LID						
Client:	Emma Day		0798				IV.										
Address:	54 Cokeham Road, Sompting W. Sx. BN15 0AG		rkc@	Drko	cltd.	.CO.U	k										
	от тольный подат, соли р ин д ти от это от о		Issue														
					J.		1	ī							\neg		-
			13.04.2022	05.12.2024													
issued for informat	ion for estimate works to price the build		04.	12.													
			13	05													
	ing C Construction Information P Preliminary T Tender SE Struc Eng	Reason	BR														
	Title		DWG		visio	ns		-							_		
	Existing Site, Location and Block Plans	2500	BR1			-		_	-								
	Proposed Driveway Level Adjustment Plans Church Flint Wall Removal	1:50 1:50	BR1	T-1		-	- }	-	-						\dashv	-	
	Proposed Front Garden GA Plans	1:50	SS	- 11		\dashv	\dashv	-	-						\dashv		
	Existing Foundation General Arrangement Plan	1:50	BR1	T1		-	\dashv	_	_	-					\dashv		
	Existing Ground Floor General Arrangement Plan	1:50	BR1		\dashv	\dashv	\dashv	寸	_	一				\dashv	ᅥ		
	Existing Roof General Arrangement Plan	1:50	BR1	T1		一	十	┪		_					寸		
	Proposed Foundation Demolition Plan	1:50		T1		寸	丁	T							寸		
201554 - A - 111	Proposed Ground Floor Demolition Plan	1:50	BR1	T1		丁				1					⇉		
201554 - A - 112	Proposed First Floor Demolition Plan	1:50	BR1														
	Proposed Foundation General Arrangement Plan	1:50	BR1														
	Proposed Ground Floor General Arrangement Plan	1:50		T1				_[[[
	Proposed First Floor General Arrangement Plan	1:50	BR1			[_						Ш			
	Proposed Foundations Setting Out Plan	1:50	BR1	T1				_							_		
	Proposed Ground Floor Setting Out Plan	1:50	BR1			_	_	4	_						4		
	Proposed First Floor Setting Out Plan Proposed Mechanical and Electrical Legend	1:50 NTS	BR1	T1		_	_	-	-						\dashv		
	Proposed Ground Floor Electrical Legend Proposed Ground Floor Electrical Layout	1:25	BR1	T1			-	-	_						-		
	Proposed First Floor Mechanical and Electrical Layout	1:25	BR1			\dashv	\dashv	-	-						\dashv		
	Proposed Ground Floor Plumbing Layout	1:25	BR1			-	\dashv	_	_	-					\dashv		
	Existing General Arrangement Elevations	NTS	BR1	T1		1	- t	1									
	Demolition General Arrangement Elevations	NTS	BR1	T1													
201554 - A - 220	Proposed General Arrangement Elevations	NTS	BR1	T1													
	Existing General Arrangement Sections	1:50	BR1														
	Demolition General Arrangement Sections	1:50	BR1	T1													
	Proposed Sections Sheet 01	1:50	BR1												_		
	Proposed Sections Sheet 02	1:50	BR1	T1				_							_		
	Proposed Chimney Breast Plans	1:10	BR1			_	_	-	_						_		
	Proposed Chimney Breast Strip Sections Proposed Strip Sections Sheet 01	1:10 1:10	BR1				-	-	_						-		
	Proposed Stair Plans and Sections	1:10	BR1			-	\dashv	+	-						\dashv		
	Floor Interface Details Sheet 01	1:5	BR1			-	\dashv	_	_	-					\dashv		
	Roof Interface Details Sheet 01	1:5	BR1			-	\dashv	+	_						\dashv		
	Roof Dormer Support Interface Details Sheet 02	1:5	BR1			寸	寸	寸		一				Ħ	寸		
	Roof Interface Details Sheet 03	1:5	BR1			丁				1					╗		
201554 - A - 513	Roof Penetrations Details Sheet 01	1:5	SS														
	Proposed Door Window and Roof Light Schedules	NTS	BR1														
	Proposed U Value Calculations	NTS	BR1	T1						[\Box		
	Proposed Kitchen Dining Living Area General Arrangement Plan	1:20	SS				_	4							_		
201554 - A - 900	Proposed Building Regulation Notes	NTS	BR1	11	-	_	_	4		_				Щ	4	_	
						\dashv	+	┩						H	႕	-	
59298	Structural Calculations from Third Party (Dixon Hurst)		1		H	\dashv	十	┪	+	_			H	H	\dashv	-1	
	, , , , , , , , , , , , , , , , , , ,								'								
	Name / Organisation		Copi	es / T	Гуре	/ For	mat										
	Adur Worthing Planning Dept.					_	_	_	_			Щ		Щ	_		
Estate Agent Client	Gary Evans @ Michael Jones & Bacon Lancing Emma Day - 54 Cokeham Road Sompting W. Sx. BN15 0AG				\vdash	\dashv	\dashv	+	_		_			\vdash	\dashv	-	
	West Sussex Building Control		Е			\dashv	\dashv	\dashv		-					\dashv		
Kitchen	Kitchen Designer					寸	寸	7						Ħ	一		
QS	•														ゴ		
S. Engineer	Dixon Hurst Consulting Civil & Structural Engineers				П	_[\bot	Į		二				Ш	긔		\Box
M Contractor				Е													



 Scale: 1:100
 Scale: 1:50

 0m
 1m
 2m
 3m
 4m
 5m
 6m
 7m
 8m
 0m
 1m
 1m
 2m
 3m
 3m
 4m

It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance.

Drawing Referencing Legend
Title Reference Bubble NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are Drawing Referencing Legend
Title Reference Bubble Detail reference n° on current sheet:

referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

xx Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°. Refers to room elevation or Denotes dwg n° for forward detailed dwg referencing
Elevation (inc. room elevations) Reference Bubble of area. Reference n°: refers to top n° of Title bubble on residing dwg n°.
Denotes dwg n° for forward referencing Arrow denotes direction of view or face of referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward

referencing

Loop encloses
area subject
to detail to detail referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°.
Denotes dwg n° for forward • XX direction of view or face of referencing subject Section Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of view or face of subject Typical General Arrangement DWG N° Key
Stage: 1-Existing, 2-Demolition

3+ -Proposals
Job N°

521717-A-121-0 0= Extents
1-5= Zones Discipline (A= Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions. WWW.RKCCLTD.CO.UK 07985585488 RKC@RKCCLTD.CO.UK DESIGN ARCHITECTURE ENGINEERING CONSTRUCTION PLANNING SCHEDULING ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL ENGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL NOT ENDER 0 Emma Day 54 Cokeham Road Sompting TION Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Existing

NO General Arrangement

0

Drawn by: 1:50@A1, 1:100@A3 RKC 13.04.22 Checked by: Designed by: Approved by: RKC

Foundation

Plan

File Ref.: 201554-A-100.DWG - T1-241205142959 24:12:05:14:30:00 Drawing No. 201554-A-100

DRAWIN

FROM

BUILD

10

CONSTRUCTION

FOR

DRAW

FROM

<u>N</u>

0

CONSTRUCTION

FOR

10

Existing Ground Floor General Arrangement Plan

Scale: 1:50@A1

It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance. NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are Room Reference Legend
Denotes Room name Room
Denotes Level G - 01 G - 01 Denotes room n° Denotes room area Drawing Referencing Legend

Title Reference Bubble

Detail reference n° on current sheet:
referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°. Denotes dwg n° for *forward* referencing
Elevation (inc. room elevations) Reference Bubble Elevation (*Inc. room elevauoris*) necessions Salarian Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for *forward* referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title — Loop end. bubble on residing dwg n°.
Denotes dwg n° for forward referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title •XX bubble on residing dwg n°.
Denotes dwg n° for forward • XX referencing Section Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°. Denotes dwg n° for forward referencing Typical General Arrangement DWG N° Key
Stage: 1-Existing, 2-Demolition—Sheet series N°:
3+ -Proposals
Job N°—521717-A-121-0
0= Extents
1-5= Zones Discipline (A= Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions. T1 05.12.24 RKC - DRAWING ISSUED FOR TENDER
Rev Date By Chk Comment WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL ENGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL NOT ENDER 0 Emma Day 54 Cokeham Road Sompting TION Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Existing NO **Ground Floor** General Arrangement Plan Drawn by: 0 RKC 1:50@A1, 1:100@A3 Checked by: Designed by:

Refers to room elevation or

detailed dwg

Arrow denotes direction of view or face of

to detail

Arrow denotes

Arrow denotes

view or face of subject

direction of

13.04.22

Approved by:

24:12:05:14:30:37

RKC

Drawing No.

201554-A-101

File Ref.: 201554-A-101.DWG - T1-241205143037

direction of view or face of

subject

of area.

DRAWING

THIS

FROM

BUILD

NOT

0

CONSTRUCTION

FOR

NOT

DRAW

FROM

NOT

0

CONSTRUCTION


FOR

10

All dimensions prefixed by * and suffixed by * are dimensions to the existing fabric and are subject to site checking prior to commencement of construction, manufacture or installation. All discrepancies to be reported to RKCC immediately on discovery.

 Scale: 1:100
 Scale: 1:50

 0m
 1m
 2m
 3m
 4m
 5m
 6m
 7m
 8m
 0m
 1m
 1m
 2m
 3m
 3m
 4m



O1 Existing Roof / First Floor General Arrangement Plan
Scale: 1:50@A1

It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance.

Drawing Referencing Legend
Title Reference Bubble
Detail reference n° on current sheet:
referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title
backward referencing only
Room Call Out Reference Bubble NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward

referencing Refers to room elevation or detailed dwg referencing
Elevation (inc. room elevations) Reference Bubble of area. Arrow denotes direction of view or face of referencing
Detail Call Out Reference Bubble
Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward
referencing

Section Detail Reference Bubble
Reference n°: refers to top n° of Title

XXX

area subject
to detail Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward Arrow denotes direction of view or face of referencing subject Section Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°. direction of view or face of subject Typical General Arrangement DWG N° Key
Stage: 1-Existing, 2-Demolition

3+ -Proposals
Job N°
Discipline (A= Architecture)

Typical General Arrangement DWG N° Key
Sheet series N°:
0= Extents
1-5= Zones
Dwg Series All details referenced in call outs supercede general arrangement or larger depictions. WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL ENGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL NOT TENDER 0 Emma Day 54 Cokeham Road Sompting CTION Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory CONSTRU and Kitchen Extension Existing Roof / First Floor General Arrangement Plan

OR

Drawn by: RKC

Designed by:

RKC

201554-A-102

Drawing No.

File Ref.: 201554-A-102.DWG - T1-241205143113

1:50@A1, 1:100@A3

Checked by:

13.04.22

Approved by:

24:12:05:14:31:13

All dimensions prefixed by * and suffixed by * are dimensions to the existing fabric and are subject to site checking prior to commencement of construction, manufacture or installation. All discrepancies to be reported to RKCC immediately on discovery.

DRAWING

THIS

FROM

BUILD

NOT

0

CONSTRUCTION

FOR

NOT

DRAW

THIS

FROM


BUILD

NOT

0

CONSTRUCTION

FOR



It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance.

Drawing Referencing Legend Title Reference Bubble NOTES: Do not scale this drawing. All dimensions to be checked on site prior to ommencement or manufacture. PLANNING dwgs: All elements or entities shown are Drawing Referencing Legend
Title Reference Bubble Detail reference n° on current sheet: referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

• xx | Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room bubble on residing dwg n°. elevation or •XX Denotes dwg n° for forward ——— detailed dwg referencing of area. Elevation (inc. room elevations) Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. ∠
Denotes dwg n° for *forward* **←**XX direction of view or face of referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward — referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°. direction of Denotes dwg n° for *forward*——— view or face of referencing subject Section Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for forward view or face of Typical General Arrangement DWG N° Key Level N° —Sheet series N°: Stage: 1-Existing, 2-Demolition——— 3+ -Proposals 521717-A-121-0 0= Extents Job N° Zones Discipline (A = Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUI NOT 0Emma Day 54 Cokeham Road Sompting 0roject Title Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Demolition Foundation General Arrangement RKC :50@A1, 1:100@A3 13.04.22 Checked by: Approved by: Designed by: RKC File Ref.: X\201554-BREGS\GA\1UU\ 201554-A-110.DWG - T1-241205143150 24:12:05:14:31:51 Drawing No. 201554-A-110

aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance. NOTES: Do not scale this drawing. All dimensions to be checked on site prior to ommencement or manufacture. PLANNING dwgs: All elements or entities shown are Room Reference Legend
Denotes Room name Room
Denotes Level G - 01 G - 01 Denotes room n° Denotes room area Title Reference Bubble Detail reference n° on current sheet: referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

• xx | Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room bubble on residing dwg n°. elevation or •XX Denotes dwg n° for forward ——— detailed dwg referencing of area. Elevation (inc. room elevations) Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward Arrow denotes direction of view or face of referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for *forward* referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for forward——— view or face of referencing subject Section Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for forward view or face of Typical General Arrangement DWG N° Key Level N° —Sheet series N°: Stage: 1-Existing, 2-Demolition——— 3+ -Proposals 521717-A-121-0 0= Extents Zones Discipline (A= Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions 05.12.24 RKC - DRAWING ISSUED FOR TENDER WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL NOT 0Emma Day 54 Cokeham Road Sompting 0 roject Title Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Ground Floor


It is the responsibility of the Contractor to manage the Health and Safety

Demolition

RKC :50@A1, 1:100@A3 13.04.22 Checked by: Approved by: Designed by: RKC File Ref.: 201554-A-111.DWG - T1-241205143230

24:12:05:14:32:30 Drawing No. 201554-A-111

All dimensions prefixed by * and suffixed by * are dimensions to the existing fabric and are subject to site checking prior to



It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance.

Drawing Referencing Legend
Title Reference Bubble NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are Drawing Referencing Legend
Title Reference Bubble backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room bubble on residing dwg n°. elevation or Denotes dwg n° for forward detailed dwg referencing
Elevation (inc. room elevations) Reference Bubble Elevation (*Inc. room elevations*) notes and Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for *forward* Arrow denotes direction of view or face of referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward —— referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°.
Denotes dwg n° for forward direction of view or face of referencing subject Section Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°. direction of view or face of Typical General Arrangement DWG N° Key
Stage: 1-Existing, 2-Demolition

3+ -Proposals
Job N°

521717-A-121-0 0= Extents
1-5= Zones Discipline (A = Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions. WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL NOT |Emma Day 54 Cokeham Road Sompting Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Roof / First Floor NO Demolition RKC :50@A1, 1:100@A3 13.04.22

Drawn by: Scale: Date:
1:50@A1, 1:100@A3 13.04.22

Designed by: Checked by: Approved by:
RKC - -


File Ref.: X\201554-BREGS\GA\100\
201554-A-112.DWG - T1-241205143307

24:12:05:14:33:07


Drawing No.


201554-A-112

Rev.
T1




It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer".






It is the responsibility of the Contractor to manage the Health and Safety

ommencement of construction, manufacture or installation. All discrepancies to be reported to RKCC immediately on discovery. | with specialist manufacturers design and details





It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance. NOTES: Do not scale this drawing. All dimensions to be checked on site prior to ommencement or manufacture. PLANNING dwgs: All elements or entities shown are Room Reference Legend
Denotes Room name Room
Denotes Level G - 01 G - 01 — Denotes room n° Denotes room area Drawing Referencing Legend Title Reference Bubble Detail reference n° on current sheet: referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

• xx | Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room bubble on residing dwg n°. elevation or Denotes dwg n° for forward ———— •XX detailed dwg referencing of area. Elevation (inc. room elevations) Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward Arrow denotes **←**XX direction of view or face of referencing


Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward to detail referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of view or face of Denotes dwg n° for *forward*——— subject referencing Section Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for forward view or face of subject Typical General Arrangement DWG N° Key —Level N° —Sheet series N°: Stage: 1-Existing, 2-Demolition———— 3+ -Proposals 521717-A-121-0 0= Extents Zones Discipline (A= Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depiction T1 05.12.24 RKC - Gen revs. Clouds omitted for clarity
Rev Date By Chk Comment WWW.RKCCLTD.CO.UK 07985585488 ESIGN ARCHITECTURE ENGINEERING CONSTRUCTION PLANNING SCHEDULING ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL ENGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL ENDER Emma Day 54 Cokeham Road Sompting Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Proposed NO **Ground Floor** Setting Out Plan Drawn by: RKC 1:50@A1, 1:100@A3 13.04.22 Checked by: Designed by: Approved by: RKC File Ref.: 201554-A-131.DWG - T1-241205143627 24:12:05:14:36:26 Drawing No.

NOT 0 TION

201554-A-131



It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance. NOTES: Do not scale this drawing. All dimensions to be checked on site prior to ommencement or manufacture. PLANNING dwgs: All elements or entities shown are G - 01 Denotes room n° Denotes room area Drawing Referencing Legend Title Reference Bubble backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room -XX bubble on residing dwg n°. elevation or detailed dwg Denotes dwg n° for forward referencing
Elevation (inc. room elevations) Reference Bubble of area. Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward Arrow denotes direction of view or face of referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title bubble on residing dwg n°.

Denotes dwg n° for forward —— to detail referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. → XX direction of Denotes dwg n° for *forward*—— view or face of referencing subject Section Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for forward view or face of referencing subject Typical General Arrangement DWG N° Key Level N° Stage: 1-Existing, 2-Demolition —Sheet series N°: 3+ -Proposals 521717-A-121-0 0= Extents Zones All details referenced in call outs supercede general arrangement or larger depictions T1 05.12.24 RKC - Gen revs. Clouds omitted for clarity
Rev Date By Chk Comment WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING BUIL NOT ENDER 0 Emma Day 54 Cokeham Road Sompting TION **Roof Extension** and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Proposed NO First Floor Setting Out Plan Drawn by: 0 RKC :50@A1, 1:100@A3 13.04.22 Checked by: Designed by: Approved by: RKC File Ref.: X:\201554-BREGS\GA\100\ 201554-A-132.DWG - T1-241205143707 24:12:05:14:37:07 Drawing No. 201554-A-132

All Mechanical & Electrical and Structural information shown indicative only. Please refer to Mechanical & Electrical and Structural documentation.

DP DOUBLE POLE

TP TRIPLE POLE

4P 4 POLE

P.F POWER FACTOR

D.O.L DIRECT ON LINE

S.D STAR DELTA

S/ST SOFT START

CONT CONTACTOR

Trans TRANSMFORMER

HV HIGH VOLTAGE

DC DIRECT CURRENT

UG UNDERGROUND

INDICATOR

SPN SINGLE POLE & NEUTRAL

CL CLEANERS

PHASE OF SUPPLY

DATA

OUTLET

TWIN DATA OUTLET

TELEPHONE OUTLET

WIFI OUTLET

FAX OUTLET

FM OUTLET

TV OUTLET

DATA OUTLET

SATELLITE OUTLET

TEXT GENERAL

H/L HIGH LEVEL

L/L LOW LEVEL

W/H WORKTOP HEIGHT

D/M DADO TRUNKING MOUNTED

AFFL ABOVE FINISHED FLOOR LEVEL

AGL ABOVE GROUND LEVEL

BGL BELOW GROUND LEVEL

ACB AIR CIRCUIT BREAKER

OCB OIL CIRCUIT BREAKER

MCB MINIATURE CIRCUIT BREAKER

CURRENT DEVICE

RCD RESIDUAL CURRENT DEVICE

F/SW FUSED SWITCH

ISOL ISOLATOR

BC BUS COUPLER

C/O CHANGEOVER

O/L OVERLOAD

E/F EARTH FAULT

SP SINGLE POLE

SW/F SWITCHED FUSE UNIT

MCCB MOULDED CASE CIRCUIT BREAKER

RCBO COMBINED MINIATURE CIRCUIT BREAKER AND RESIDUAL

NA NON-AUTO (I.E. NO TRIP) VERSION OF CIRCUIT BREAKER.

SD SWITCHED DISCONNECTOR (ON LOAD ISOLATOR)

F.A FROM ABOVE

F.B FROM BELOW

T.A TO ABOVE

T.B TO BELOW

C/V CEILING VOID

F/F FLUSH IN FLOOR

F/M FLOOR MOUNTED

It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to ommencement or manufacture. <u>PLANNING</u> dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or onstruction reality & constraints tolerance of $\pm 300 \text{mm}$ in any direction or distance. \forall TPN TRIPLE POLE & NEUTRAL M_0 C.T CURRENT TRANSFORMER Δ I/ST INVERTER CONTROL \square $\overline{0}$ CPC CIRCUIT PROTECTIVE CONDUCTOR 0HRC HIGH RUPTURING CAPACITY PME PROTECTIVE MULTIPLE EARTHING PEN COMBINED PROTECTIVE AND NEUTRAL CONDUCTORS LV LOW VOLTAGE GREATER THAN ELV TRU ELV EXTRA LOW VOLTAGE FELV FUNCTIONAL EXTRA LOW VOLTAGE 5 PELV PROTECTIVE EXTRA LOW VOLTAGE SELV SEPARATED EXTRA LOW VOLTAGE 0AC ALTERNATING CURRENT 0 UPS UNINTERRUPTIBLE POWER SUPPLY

0ADJACENT LIGHT SWITCH OR FCU INDICATES NEON All details referenced in call outs supercede general arrangement or larger depictions T1 05.12.24 RKC - DRAWING ISSUED FOR TENDER
Rev Date By Chk Comment

WWW.RKCCLTD.CO.UK 07985585488

ESIGN ARCHITECTURE ENGINEERING CONSTRUCTION PLANNING SCHEDULING ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURA NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT COM ESTIMATING

Emma Day 54 Cokeham Road Sompting

BUI

NOT

0

0

 \bigcirc

Z

0

Drawing Title

roject Title

Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension

Proposed Mechanical & Electrical Legend


Drawn by RKC NTS 13.04.22 Designed by: Checked by: Approved by: RKC


File Ref.: 201554-A-140.DWG - T1-241205143743 24:12:05:14:37:42 Drawing No. 201554-A-140

All specialist equipment installed in accordance with specialist manufacturers design and details

0

NOT





It is the responsibility of the Contractor to manage the Health and Safety



It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: DO not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. <u>PLANNING</u> dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance. NOTES: Do not scale this drawing. All dimensions to be checked on site prior to NOTE: These elevations are indicative ONLY. Do NOT scale Refer to dimensioned plans, sections and details ONLY i-----FINISHES & MATERIALS LEGEND 1. Existing reddish blend clay tiles 2. Existing White painted rough shingle pebble dash render 3. Unpainted concrete blockwork 4. Unpainted clay brickwwork 5. Reddish blend clay tiles to match existing 6. Painted fine sand render Drawing Referencing Legend

Title Reference Bubble

Detail reference n° on current sheet:
referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room -XX bubble on residing dwg n°. elevation or Denotes dwg n° for forward detailed dwg referencing
Elevation (inc. room elevations) Reference Bubble of area. Reference n°: refers to top n° of Title bubble on residing dwg n°.
Denotes dwg n° for forward xxx Arrow denotes **←**XX direction of view or face of referencing


Detail Call Out Reference Bubble


Reference n°: refers to top n° of Title — Loup end. bubble on residing dwg n°.


Denotes dwg n° for forward — to detail referencing
Section Detail Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°.
Denotes dwg n° for forward direction of view or face of subject Section Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of view or face of subject Typical General Arrangement DWG N° Key
Stage: 1-Existing, 2-Demolition


3+ -Proposals
Job N°


521717-A-121-0 0= Extents
1-5= Zones Discipline (A= Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions. T1 05.12.24 RKC - DRAWING ISSUED FOR TENDER
Rev Date By Chk Comment WWW.RKCCLTD.CO.UK 07985585488 ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS COSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL ENGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING ENDER Emma Day 54 Cokeham Road Sompting **Roof Extension** and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension Existing General Arrangement Elevations NTS 13.04.22 Checked by: Approved by: File Ref.: X:\201554-BREGS\GA\200\
201554-A-200.DWG - T1-241205144502 24:12:05:14:45:21











Existing

General Arrangement Sections

:50@A1, 1:100@A3

Checked by:

13.04.22

Approved by:

24:12:05:14:47:43

NO

0

Drawn by:

RKC

Designed by:

RKC

Drawing No.

201554-A-300

File Ref.: X\201554-BREGS\GA\300\ 201554-A-300.DWG - T1-241205144743

 Scale: 1:100
 Scale: 1:50

 0m
 1m
 2m
 3m
 4m
 5m
 6m
 7m
 8m
 0m
 1m
 1m
 2m
 3m
 3m
 4m

All dimensions prefixed by * and suffixed by * are dimensions to the existing fabric and are subject to site checking prior to commencement of construction, manufacture or installation. All discrepancies to be reported to RKCC immediately on discovery.

DRAWIN

THIS

FROM

BUILD

<u>N</u>

0

CONSTRUCTION

FOR

DRAW

FROM


<u>N</u>

0

CONSTRUCTION

FOR

10



It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer". NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance. ommencement or manufacture. PLANNING dwgs: All elements or entities shown are Title Reference Bubble Detail reference n° on current sheet: referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

• xx | Scale: 1:1 backward referencing only
Room Call Out Reference Bubble Reference n°: refers to top n° of Title Refers to room bubble on residing dwg n°. elevation or •XX Denotes dwg n° for forward ——— detailed dwg referencing Elevation (*inc. room elevations*) Reference Bubble Reference n°: refers to top n° of Title Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for forward ——— view or face of referencing Detail Call Out Reference Bubble Reference n°: refers to top n° of Title bubble on residing dwg n°. Denotes dwg n° for forward — | referencing | Section Detail Reference Bubble | referencing Reference n°: refers to top n° of Title bubble on residing dwg n°. direction of Denotes dwg n° for forward——— view or face of Section Reference Bubble Reference n°: refers to top n° of Title •XX Arrow denotes bubble on residing dwg n°. direction of Denotes dwg n° for *forward*—— view or face of Typical General Arrangement DWG N° Key Stage: 1-Existing, 2-Demolition——— 3+ -Proposals 521717-A-121-0 0= Extents 1-5= Zones Discipline (A= Architecture) — Dwg Series All details referenced in call outs supercede general arrangement or larger depictions.

CONSTRUCTION CONSULTANCY LY
WWW.RKCCLTD.CO.UK 07985585488 RKC@RKCCLTD.CO.UK

ESIGN ARCHITECTURE ENGINEERING CONSTRUCTION PLANNING SCHEDULING ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT COM ESTIMATING

SSUED FOR

lient Emma Day 54 Cokeham Road Sompting

St Title

Roof Extension

and Enlargement of Rebuild of Existin

and Enlargement of Rebuild of Existing
Conservatory, Lean-to Conservatory
and Kitchen Extension

ing Title

Demolition


Sections


Drawn by: Scale: Date:

RKC 1:50@A1, 1:100@A3 13.04.22

Designed by: Checked by: Approved by:


RKC - -





Insulation Legend Denotes PIR solid insulation cut to tightly fill void. All edges to be snug or filled with insulating foam cut flush. Warm insulation side to accommodate VCL (Vapour Control Layer) lapped and sealed in accordance with manufacturers design and specification.

> Denotes fibre glass foam/wool insulation cut to tightly fill void. All edges to be snug. Warm insulation side to accommodate VCL (Vapour Control Layer) (where installed) lapped and sealed in accordance with manufacturers design and specification.



WWW.RKCCLTD.CO.UK 07985585488 RKC@RKCCLTD.CO.UK ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS

It is the responsibility of the Contractor to manage the Health and Safety

aspects of the project or nominate and agree a "Principle Designer".

ommencement or manufacture. PLANNING dwgs: All elements or entities shown are

indicative in shape, size and location and are subject to a manufacturers and/or nstruction reality & constraints tolerance of ± 300 mm in any direction or distance.

NOTES: Do not scale this drawing. All dimensions to be checked on site prior to

DR

RO

Drawing Referencing Legend

Detail reference n° on current sheet:

Reference n°: refers to top n° of Title

Denotes dwg n° for forward ———

Reference n°: refers to top n° of Title

Detail Call Out Reference Bubble Reference n°: refers to top n° of Title —

Denotes dwg n° for forward —

Denotes dwg n° for forward—

Denotes dwg n° for forward———

Section Reference Bubble

Reference n°: refers to top n° of Title •XX

Reference n°: refers to top n° of Title •XX

Typical General Arrangement DWG N° Key Stage: 1-Existing, 2-Demolition————

Denotes dwg n° for forward —

Elevation (*inc. room elevations*) Reference Bubble

bubble on residing dwg n°.

backward referencing only
Room Call Out Reference Bubble

referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

• xx | Scale: 1:1

Refers to room

elevation or

detailed dwg

Arrow denotes

view or face of

direction of

view or face of

Arrow denotes

view or face of

direction of

direction of

Title Reference Bubble

referencing

referencing

bubble on residing dwg n°.

referencing Section Detail Reference Bubble

> OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING

Emma Day 54 Cokeham Road Sompting

BUII

NOT

0

Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory

and Kitchen Extension

Proposed

Sections Sheet 01

0	RKC	1:50@A1, 1:100@A3	13.04.22
<u>Ч</u>	Designed by: RKC	Checked by: -	Approved by: -
\overline{C}	File Ref.: X:\201554-BREGS\GA'	,300\ - T1-241205144920	24:12:05:14:49:24

201554-A-320

Screed depths may vary depending on floor finish and location. Main Contractor to determine screed depth required for each location to accommodate floor finish, underlay, membranes, paints, fixings, etc to maintain uniform finished floor levels. Contractor to allow for a self levelling screed throughout.

DRAW

FROM

<u>N</u>

0

CONSTRUCTION

0

All dimensions prefixed by * and suffixed by * are dimensions to the existing fabric and are subject to site checking prior to mmencement of construction, manufacture or installation. All discrepancies to be reported to RKCC immediately on discovery. | with specialist manufacturers design and details

 Scale: 1:100
 Scale: 1:50

 0m
 flm
 2m
 3m
 4m
 5m
 6m
 7m
 8m
 0m
 flm
 2m
 3m
 4m

AW

 $\overline{0}$

CONSTRUCTION

DRAW


FROM

0

0

CONSTRUCTION

0



Insulation Legend Denotes PIR solid insulation cut to tightly fill void. All edges to be snug or filled with insulating foam cut flush. Warm insulation side to accommodate VCL (Vapour Control Layer) lapped and sealed in accordance with manufacturers design and

specification. Denotes fibre glass foam/wool insulation cut to tightly fill void. All edges to be snug. Warm insulation side to accommodate VCL (Vapour Control Layer) (where installed) lapped and sealed in accordance with

manufacturers design and specification.

Conservatory, Lean-to Conservatory and Kitchen Extension Drawing Title Proposed Sections Sheet 02 Drawn by: :50@A1, 1:100@A3

roject Title

BUI

NOT

0

0

13.04.22 Checked by: Approved by: Designed by: File Ref.: X:\201554-BREGS\GA\300\
201554-A-321.DWG - T1-241205145010 24:12:05:14:50:12 Drawing No. 201554-A-321

It is the responsibility of the Contractor to manage the Health and Safety

aspects of the project or nominate and agree a "Principle Designer".

commencement or manufacture. PLANNING dwgs: All elements or entities shown are

indicative in shape, size and location and are subject to a manufacturers and/or nstruction reality & constraints tolerance of ± 300 mm in any direction or distance.

NOTES: Do not scale this drawing. All dimensions to be checked on site prior to

AWIN

DR

ROM

Title Reference Bubble

referencing

Detail reference n° on current sheet:

Reference n°: refers to top n° of Title

Denotes dwg n° for forward ———

Reference n°: refers to top n° of Title

Denotes dwg n° for forward ————

referencing

Detail Call Out Reference Bubble

Reference n°: refers to top n° of Title —

bubble on residing dwg n°.

bubble on residing dwg n°. Denotes dwg n° for forward referencing
Section Detail Reference Bubble

bubble on residing dwg n°.

bubble on residing dwg n°.

Elevation (*inc. room elevations*) Reference Bubble

Reference n°: refers to top n° of Title

Reference n°: refers to top n° of Title

Typical General Arrangement DWG N° Key

Stage: 1-Existing, 2-Demolition———

Discipline (A= Architecture)

3+ -Proposals 521717-A-121-0 0= Extents Zones

All details referenced in call outs supercede general arrangement or larger depictions

WWW.RKCCLTD.CO.UK 07985585488 RKC@RKCCLTD.CO.UK

ROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS OSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL NGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING

ENDER

Emma Day

54 Cokeham Road

Sompting

Roof Extension

and Enlargement of Rebuild of Existing

Denotes dwg n° for *forward*———

Denotes dwg n° for forward———

Section Reference Bubble

bubble on residing dwg n°.

backward referencing only
Room Call Out Reference Bubble

referred to by top n° of other bubbles.

Denotes dwg n° of sheet for Title

• xx | Scale: 1:1

Refers to room

elevation or

of area.

detailed dwg

Arrow denotes

view or face of

Arrow denotes

view or face of subject

Arrow denotes

view or face of subject

direction of

—Level N° —Sheet series N°:

direction of

direction of

•XX


←XX


Screed depths may vary depending on floor finish and location. Main Contractor to determine screed depth required for each location to accommodate floor finish, underlay, membranes, paints, fixings, etc to maintain uniform finished floor levels. Contractor to allow for a self levelling screed throughout.


All dimensions prefixed by * and suffixed by * are dimensions to the existing fabric and are subject to site checking prior to mmencement of construction, manufacture or installation. All discrepancies to be reported to RKCC immediately on discovery. | with specialist manufacturers design and details


 Scale: 1:100
 Scale: 1:50


 0m
 flm
 2m
 3m
 4m
 5m
 6m
 7m
 8m
 0m
 flm
 2m
 3m
 4m




















Proposed Door Schedule Scale: NTS 201554

	. 2	01554															Door So	hedule					
<	Aperture	Level R	Room As	ssembly	Room				Door Leaf	Door Leaf	Door Leaf	Fire	Sound			Vision Panel	Vision Panel						
\propto	Code	N°	N°	N°	Name	SO Heigh	t SO Width	n SO Depth	Height	Width	Thickness	Rating	Rating dB	Door Finish	Frame Finish	Height	Width	Kick Plates	Access Control (Locks)	Ironmongery	Assemble Type	NBS Ref	Notes
	D	01	01	01	Hall	2035	860	250	tbc	tbc	tbc	n/a	n/a	PVCu Grey	PVCu Grey	tbc	tbc	n/a	Multi point euro cylinder with latch	tbc	tbc	L20, L40	-
	D	01	01	02	Hall	3xTBC	3x500	3x125	3xTBC	3x426	tbc	n/a	n/a	Timber painted	Timber painted	n/a	n/a	n/a	tbc	tbc	tbc	L20, L40 Cup'd do	oors 3 No High to suit shelves
\mathcal{O} .	D	01	01	05	Hall	1695	610	125	1650	526	25	n/a	n/a	Timber painted	Timber painted	n/a	n/a	n/a	n/a	tbc	tbc	L20, L40	-
	• D	01	01	05	Hall	800	600	125	755	526	25	n/a	n/a	Timber painted	Timber painted	n/a	n/a	n/a	3 lever Deadlock	tbc	tbc	L20, L40	-
\Box	1 1 1	01	03	01	TV Room	2085	800	125	2040	726	25	n/a	n/a	Timber painted	Timber painted	n/a	n/a	n/a	n/a	tbc	tbc	L20, L40	-
—		01	04	01	Bed 3	2085	900	125	2040	826	40	n/a	n/a	Timber painted	Timber painted	n/a	n/a	n/a	Sashlock	tbc	tbc	L20, L40	-
	D	01	06	01	Kitchen	2085	1000	125	2040	926	40	30	n/a	Timber painted	Timber painted	n/a	n/a	n/a	n/a	tbc	tbc	L20, L40	-
\geq	D	01	08	01	Bath	2085	700	125	2040	626	25	n/a	n/a	Timber painted	Timber painted	n/a	n/a	n/a	Twist lock	tbc	tbc	L20, L40	-
		01	09	01	Utility	2040	965	300	tbc	tbc	tbc	n/a	n/a	PVCu Grey	PVCu Grey	2x450	2x150	n/a	Keyed security locks	tbc	tbc	L20, L40	-
		01	10	01	Garage	2040	910	300	tbc	tbc	tbc	n/a	n/a	PVCu Grey	PVCu Grey	n/a	n/a	n/a	Keyed security locks	tbc	Insulated PVCu	L20, L40	_
Δ	D	01	10	02	Garage	1985	2140	100	tbc	tbc	tbc	n/a	n/a	Metal Grey	Metal Hidden	n/a	n/a	n/a	Keyed security locks	tbc	tbc	L20, L40	_
Ш	D	02	01	01	Landing	878	800	115	830	726	40	n/a	n/a	Painted timber	Painted timber	n/a	n/a	n/a	Spring latches	tbc	tbc	L20, L40	_
	D	02	02	01	Bed 2	2020	800	125	1981	726	40	n/a	n/a	Painted timber	Painted timber	n/a	n/a	n/a	Sashlock	tbc	tbc	L20, L40	_
	D	02	03	01	Bed 1	2020	800	125	1981	726	40	n/a	n/a	Painted timber	Painted timber	n/a	n/a	n/a	Sashlock	tbc	tbc	L20, L40	_
	D	02	04	01	Bath	2085	800	125	2040	726	40	n/a	n/a	Painted timber	Painted timber	n/a	n/a	n/a	Sashlock	tbc	tbc	L20, L40	_
\triangle																							
\vdash	•																						
$\dot{\Box}$																							
\subseteq																							

Proposed Window Schedule Scale: NTS

	201	1554	Window Schedule																				
Z	perture l	Level Ro	oom A	ssembly	Room				Window Leaf	Window Leaf	Window Leaf	Fire	Sound			Vision Panel	Vision Panel	Precautionary					
	Code	N°	N°	N°	Name	SO Height	SO Width	SO Depth	Height	Width	Thickness	Rating	Rating dB	Window Finish	Frame Finish	Height	Width	Glass	Access Control (Locks)	Ironmongery	Assemble Type	NBS Ref	Notes
[W	01	02	01	Bed 4	1240	2420	250	tbc	tbc	tbc	n/a	n/a	PVCu Grey	tbc	tbc	tbc	n/a	Keyed multi point lockable	tbc	3 Panel Bay	L10, L40 Bay Win	ndows to be Colur Treated to Gre
⊢	W	01	04	01	Bed 3	1240	2420	250	tbc	tbc	tbc	n/a	n/a	PVCu Grey	tbc	tbc	tbc	n/a	Keyed multi point lockable	tbc	3 Panel Bay	L10, L40 Bay Win	ndows to be Colur Treated to Gre
\bigcirc	W	01	05	01	Living	2135	3485	337	2100	3465	tbc	n/a	n/a	PVCu Grey	tbc	tbc	tbc	Safety glass	Keyed multi point lockable	tbc	5 Glazed panel bifold door with flush cill track inc 1 access door to end panel	L10, L40 2 Slidin	ng Panel 1 OPening Panel Patio [
	W	01	06	01	Kitchen	2135	3485	337	2100	3465	tbc	n/a	n/a	PVCu Grey	tbc	tbc	tbc	Safety glass	Keyed multi point lockable	tbc	4 Glazed panel bifold door with flush cill track inc 1 access door to end panel	L10, L40 2 Slidin	ng Panel 1 OPening Panel Patio [
	W	01	09	01	Utility	1100	440	343	430	323	tbc	n/a	n/a	PVCu Grey	Frosted	250	300	n/a	Keyed multi point lockable	yes	tbc	L10, L40	-
	W	02	01	01	Landing	2025	573	232	2015	560	tbc	n/a	n/a	PVCu Grey	Clear	2015	560	n/a	Yes	Yes	Top hung mechanically opening from qtr landing	L10, L40	-
-	W	02	02	01	Bed 2	1075	1135	232	1065	1340	tbc	n/a	n/a	PVCu Grey	Clear	tbc	tbc	n/a	Yes	No	2 side opening panels with 2 opening fans lights over	L10, L40	-
\mathcal{S}	W	02	02	02	Bed 2	1075	1585	232	1065	1575	tbc	n/a	n/a	PVCu Grey	Clear	tbc	tbc	n/a	tbc	tbc	2 side opening panels with 2 opening fans lights over	L10, L40	-
	W	02	03	01	Bed 1	2025	2132	232	2015	2122	tbc	n/a	n/a	PVCu Grey	Clear	tbc	tbc	Yes	Yes	n/a	French doors with side panel TBC	L10, L40	-
	W	02	03	02	Bed 1	1075	1135	232	1065	1340	tbc	n/a	n/a	PVCu Grey	Clear	tbc	tbc	n/a	Yes	No	2 side opening panels with 2 opening fans lights over	L10, L40	-
\mathcal{O}	W	02	04	01	Bath	1075	572	232	1065	188	tbc	n/a	n/a	PVCu Grey	upto 1500mm abo	Yes	yes	No	Yes	n/a	Single side opening panel	L10, L40	-
\bigcirc																							
\simeq																							

Proposed Rooflight Schedu

FROM

NOT

0

CONSTRUCTION

FOR

NOT

ı [2	01554												·		Rooflights	Schedule					
	Aperture	Level	Room	Assembly	Room				Rooflight	Rooflight	Rooflight Leaf	Fire So	nd Rooflight F	ame Rooflight Glass	Glass Panel	Glass Panel	Precautionary					
∟ك	Code	N°	N°	N°	Name	SO Height	SO Width	SO Depth	Leaf Height	Leaf Width	Thickness	Rating Ratin	g dB Finish	Finish	Height	Width	Glass	Access Control (Locks)	System	Assemble Type	NBS Ref	Notes
/	R	01	06	01	Kitchen	1500	1000	485	1500	1000	120	n/a n	a PVCu Gr	y clear	tbc	tbc	tbc	tbc	tbc	tbc	L10, L40	_
= L	R	02	01	01	Landing	1516	700	235	1400	660	130	n/a n	a Grey	Clear	tbc	tbc	n/a	tbc	Velux GPL	Velux GPL FK08 2070	L10, L40	_
>_	R	02	01	02	Landing	1516	700	235	1400	660	130	n/a n	a Grey	Clear	tbc	tbc	n/a	tbc	Velux GPL	Velux GPL FK08 2070	L10, L40	-
<u> </u>	R	02	03	01	Bed 1	1516	700	235	1400	660	130	n/a n	a Grey	Clear	tbc	tbc	n/a	tbc	Velux GPL	Velux GPL FK08 2070	L10, L40	-
$\mathcal{I}_{oxedsymbol{oxedsymbol{\mathcal{I}}}}$																						
\subseteq																						
\neg \Box																						
┛□																						
\sim \Box					•																	

It is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer".

NOTES: Do not scale this drawing. All dimensions to be checked on site prior to commencement or manufacture. PLANNING dwgs: All elements or entities shown are indicative in shape, size and location and are subject to a manufacturers and/or construction reality & constraints tolerance of ±300mm in any direction or distance.

DO NOT BUILD

All details referenced in call outs supercede general arrangement or larger depictions.

All details referenced in call outs supercede general arrangement or larger depictions.

Til 06.12.24 RKC - DRAWING ISSUED FOR TENDER
Rev Date By Chk Comment

ADADIN KEVQTONIE

CONSTRUCTION CONSULTANCY LTD WWW.RKCCLTD.CO.UK DESIGN ARCHITECTURE ENGINEERING CONSTRUCTION PLANNING SCHEDULING

DESIGN ARCHITECTURE ENGINEERING CONSTRUCTION PLANNING SCHEDULING PROJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS COSTS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURAL ENGINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATING

ISSUED FOR T E N D E R

t Emma Day 54 Cokeham Road Sompting

BUIL

NOT

00

CONSTRUCTION

OR

Drawing Title

ject Title

Roof Extension

and Enlargement of Rebuild of Existing

Conservatory, Lean-to Conservatory
and Kitchen Extension

Proposed
Door & Window & Rooflight

Drawn by: Scale: Date:
RKC NTS 13.04.22

Designed by: Checked by: Approved by:
RKC - -

Schedules

File Ref.: X\201554-BRE6S\GA\600\DWG - T1-241206090134 24:12:06:09:01:37

Drawing No. Rev. T1

201554-A-600 T1

Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488 E-mail: rkc@rkccltd.co.uk

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 10:51

Filename: X:\201554-BREGS\U-Vals\201554 - 150mm Joists Flat Roof.uva (File saved: 17 Nov 2024 10:51)

Element type: Roof - Flat roof - insulation between timber joists - Calculation Method: BS EN ISO 6946

201554 - 150mm Joists Flat Roof Emma Day

54 Cokeham Road Sompting

 $\langle \langle \rangle$

 Δ

0

 \bigcirc

W. Sussex. BN15 0AG

<u>d (mm)</u> <u>λ layer</u> <u>λ bridge</u> <u>Fraction</u> <u>R layer</u> <u>R bridge</u> <u>Description</u> 0.100Vapour control layer Celotex PL4000 PBoard SW PR 1.136 FR 15-65mm 0.022 6.818 150 0.0900 XR4000 Insulation / joists 50 0.1300.385 Timber battens 19 0.130 0.146 OSB 0.200 0.030 felt

0.040

8.655

Total resistance: Upper limit: 7.395 Lower limit: 6.566 Ratio: 1.126 Average: 6.980 m²K/W

U-value (uncorrected) 0.143

U-value corrections

 $\Delta U = 0.006$ (Level 1) Air gaps in layer 3 No fixings in layer 3

0.006

0.149

 $0.15 \text{ W/m}^2\text{K}$

250 mm (total roof thickness)

J-value (corrected)

U-value (rounded)

Calculated by: Robert Cooper Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488 E-mail: rkc@rkccltd.co.uk

Rse

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 11:00

Filename: X:\201554-BREGS\U-Vals\201554 - Garage Roof.uva (File saved: 17 Nov 2024 11:00)

Element type: Roof - Flat roof - insulation between timber joists - Calculation Method: BS EN ISO 6946

201554 - Garage Roof Emma Day

 \triangleleft 54 Cokeham Road Sompting W. Sussex. BN15 0AG

Layer	<u>d (mm)</u>	<u>λ layer</u>	<u>λ bridge</u>	Fraction	R layer 0.100	R bridge	<u>Description</u> Rsi
1	10	R-value			1.800		Carpet
2	20	0.130			0.154		OSB
3	150	0.022	0.130	0.0900	6.818	1.154	Insulation / joists
4							Vapour control layer
					0.040		Rse
	180 mm	(total roof	thickness)		8.912		

Total resistance: Upper limit: 7.703 Lower limit: 6.823 Ratio: 1.129 Average: 7.263 m²K/W

Date: 16 November 2024

U-value (uncorrected) 0.138

U-value corrections Air gaps in layer 1

 $\Delta U = 0.000$ (Level 0) No fixings in layer 3

0.000

 $0.14 \text{ W/m}^2\text{K}$

Γotal ΔU Δ U-value (corrected) U-value (rounded)

Lady Lane Industrial Hadleigh, Ipswich, Suffolk IP7 6BA

Air Gap Corrections : N/A

Client : Robert Cooper, Rapid Keystone Construction Consultancy Ltd

Mechanical Fasteners : (nf = fasteners per m², Af = fasteners cross-sectional area)

 $Alpha: 0.8 \ per \ m, \ lambda \ f: 17.0000 \ W/mK, \ nf: 0.00002500 \ per \ m^2, \ Af: 8.6000 mm^2$

Lady Lane Industrial Hadleigh, Ipswich, Suffolk IP7 68A

Calculated by: Robert Cooper Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488 E-mail: rkc@rkccltd.co.uk

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 10:15

Filename: X:\201554-BREGS\U-Vals\201554 - Dormer Cheek Walls.uva (File saved: 24 Apr 2021 11:06)

Element type: Wall - Timber framed - insulation between studs - Calculation Method: BS EN ISO 6946

201554 - Dormer Cheek Walls Emma Day

Sompting W. Sussex. BN15 0AG

54 Cokeham Road

<u>Layer</u> <u>d (mm)</u> <u>λ layer</u> <u>λ bridge</u> <u>Fraction</u> <u>R layer</u> <u>R bridge</u> <u>Description</u> 12.5 0.060 Plasterboard Vapour control layer Celotex PL4000 PBoard SW PR 2.955 FR 15-65mm 0.040 2.500 100 0.150insulation / timber frame 0.1300.092Plywood sheathing Breather membrane Cavity ventilated R-value 1.000 Clay tiles

5.866

this resistance substitutes for Rse and the resistance of layers 7-8 because of the ventilated air layer (layer 7)

Total resistance: Upper limit: 5.537 Lower limit: 5.289 Ratio: 1.047 Average: 5.413 m²K/W

U-value (uncorrected) 0.185

U-value corrections Air gaps in layer 4

U-value (rounded)

 $\Delta U = 0.002$ (Level 1)

245 mm (total wall thickness)

Total ∆U 0.002 0.187 U-value (corrected) $0.19 \text{ W/m}^2\text{K}$

Calculated by: Robert Cooper Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488 E-mail: rkc@rkccltd.co.uk

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 10:59

Filename: X:\201554-BREGS\U-Vals\201554 - Insulated Pitched Roof.uva (File saved: 17 Nov 2024 10:59)

Element type: Roof - Pitched roof - insulated slope, sloping ceiling - Calculation Method: BS EN ISO

201554 - Insulated Pitched Roof

Emma Day 54 Cokeham Road

Sompting W. Sussex. BN15 0AG

<u>Layer</u>	<u>d (mm)</u>	λ layer	<u>λ bridge</u>	<u>Fraction</u>	R layer	R bridge	<u>Description</u>
					0.100		Rsi
1	40	0.022			1.818		Celotex PL4000 PBoard SW PR
FR 15-6	5mm						
2	125	0.022	0.130	0.0800	5.682	0.962	Insulation board / rafters
3	1	0.230			0.004		Sarking Felt
4	22	0.130			0.169		Timber battens
5	25	R-value					Air layer ventilated
6	30	1.000					Tiles (clay)
					0.100 #		Rse
	243 mm	(total roof	thickness)		7.874		

this resistance substitutes for Rse and the resistance of layers 5-6 because of the ventilated air layer (layer 5)

 $\Delta U = 0.000$ (Level 0)

 $0.15 \text{ W/m}^2\text{K}$

Total resistance: Upper limit: 7.032 Lower limit: 6.271 Ratio: 1.121 Average: 6.651 m²K/W

U-value (uncorrected) 0.150

U-value corrections Air gaps in layer 5

U-value (rounded)

No fixings in layer 2

Total ∆U 0.0000.150 U-value (corrected)

Calculated by: Robert Cooper Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 10:32

Filename: X:\201554-BREGS\U-Vals\201554 - External Ground Floor Masonry Wall.uva (File saved: 17 Nov 2024 10:32)

E-mail: rkc@rkccltd.co.uk

Element type: Wall - Masonry - full cavity fill: slabs Data error(s): ?? wall ties ??

201554 - External Ground Floor Masonry Wall

348 mm (total wall thickness)

0.000

Emma Day 54 Cokeham Road

> Sompting W. Sussex. BN15 0AG

<u>λ layer</u> <u>λ bridge</u> <u>Fraction</u> <u>R layer</u> <u>R bridge</u> <u>Description</u> 0.1300.032 Gypsum plaster (1000 kg/m³) 100 R-value 0.190Celcon HiSeven Concrete Block 0.022 5.000 Celotex XR4000 GenUse CFSH 110 110-200mm 0.150 Celcon Standard Concrete Block 100 R-value 0.031 0.800Render (gypsum, sand) 0.040

5.574

Total resistance: Upper limit: 5.574 Lower limit: 5.574 Ratio: 1.000 Average: 5.574 m²K/W

U-value (uncorrected) 0.179

U-value corrections Air gaps in layer 4 $\Delta U = 0.000$ (Level 0)

Total ∆U

Wall ties in layer?

U-value (corrected) U-value (rounded) $0.18 \text{ W/m}^2\text{K}$

Calculated by: Robert Cooper Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488 E-mail: rkc@rkccltd.co.uk

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 10:17

Filename: X:\201554-BREGS\U-Vals\201554 - Ground Floor Concrete Slab.uva (File saved: 24 Apr 2021 11:41)

Element type: Floor - Slab-on-ground floor - Calculation Method: BS EN ISO 6946, BS EN ISO 13370

201554 - Ground Floor Concrete Slab Emma Day

54 Cokeham Road Sompting W. Sussex. BN15 0AG

Thermal resistance of floor construction:

<u>Layer</u> <u>d (mm)</u> <u>λ layer</u> <u>λ bridge</u> <u>Fraction</u> <u>R layer</u> <u>R bridge</u> <u>Description</u> 0.170Rsi 0.043 Screed Vapour control layer 4.091 Celotex GA4000 GenUse 50-0.022 $100 \mathrm{mm}$ 4.304 <u>140 mm</u>

Total resistance: Upper limit: 4.304 Lower limit: 4.304 Ratio: 1.000 Average: 4.304 m²K/W

Ground parameters: Perimeter P: 35.29 m 49.15 m^2 Area A: P/A: 0.718

Wall thickness: 313 mm Ground type: Clay/silt ($\lambda = 1.5 \text{ W/m} \cdot \text{K}$) $0.04 \text{ m}^2\text{K/W}$

U-value without edge insulation: ΔU for vertical edge insulation: -0.0015 (depth 133 mm, thickness 25 mm, λ 0.040) U-value with edge insulation: 0.1836

U-value (rounded) 0.18 W/m²K

Calculated by: Robert Cooper Rapid Keystone Construction Consultancy Ltd www.rkccltd.co.uk Tel: 07985585488 E-mail: rkc@rkccltd.co.uk

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 11:03

Filename: X:\201554-BREGS\U-Vals\201554 - Masonry Gable Wall.uva (File saved: 17 Nov 2024 11:03)

Element type: Wall - Timber framed - insulation between studs - Calculation Method: BS EN ISO 6946

Calculated by:

U-value calculation by BRE U-value Calculator version 2.04b - Printed on 17 Nov 2024 at 10:36

Filename: X:\201554-BREGS\U-Vals\201554 - Flat Roof.uva (File saved: 17 Nov 2024 10:36)

<u>Layer</u> <u>d (mm)</u> <u>λ layer</u> <u>λ bridge</u> <u>Fraction</u> <u>R layer</u> <u>R bridge</u> <u>Description</u>

0.0900

Total resistance: Upper limit: 5.302 Lower limit: 5.069 Ratio: 1.046 Average: 5.186 m²K/W

Element type: Roof - Flat roof - insulation between timber joists - Calculation Method: BS EN ISO 6946

1.250

3.750

0.385

0.146

0.030

0.040

5.701

Robert Cooper

www.rkccltd.co.uk

E-mail: rkc@rkccltd.co.uk

Tel: 07985585488

Rapid Keystone Construction Consultancy Ltd

Celotex PL4000 PBoard SW PR

Vapour control layer

Timber firring battens

Insulation / joists

2015545 - Masonry Gable Wall

Emma Day 54 Cokeham Road Sompting

201554 - Flat Roof

54 Cokeham Road

W. Sussex. BN15 0AG

50

19

U-value (uncorrected) 0.193

U-value corrections

Air gaps in layer 4

U-value (corrected)

U-value (rounded)

Total ∆U

No fixings in layer 3

0.022

0.040

0.130

0.130

0.200

253 mm (total roof thickness)

 $\Delta U = 0.000$ (Level 2)

 $0.19 \text{ W/m}^2\text{K}$

0.000

0.193

Emma Day

Sompting

FR 15-65mm

W. Sussex. BN15 0AG

Ī	<u>Layer</u>	<u>d (mm)</u>	<u>λ layer</u>	<u>λ bridge</u>	Fraction	R layer 0.130	R bridge	<u>Description</u> Rsi
	1	25	0.022			1.136		Celotex PL4000 PBoard SW PR
I	FR 15-6	5mm						
	2							Vapour control layer
	3	100	0.022	0.120	0.150	4.545	0.833	insulation / timber frame
	4	150	0.035			4.286		Rockwool mineral wool
	5							Breather membrane
	6	10	R-value			0.190		Celcon HiSeven Concrete Block
	7	25	1.000			0.025		Render (cement, sand)
						_0.040		Rse
		310 mm	(total wall	thickness)		10.353		

Total resistance: Upper limit: 9.552 Lower limit: 8.532 Ratio: 1.120 Average: 9.042 m²K/W

U-value (uncorrected) 0.111

U-value corrections $\Delta U = 0.002$ (Level 1) Air gaps in layer 3

0.002 Total ∆U U-value (corrected)

0.113 U-value (rounded) $0.11 \text{ W/m}^2\text{K}$ Ω 0

0

 Δ

0

Emma Day 54 Cokeham Road Sompting

T1 05.12.24 RKC - Gen revs per clouds
Rev Date By Chk Comment

WWW.RKCCLTD.CO.UK 07985585488

DJECT MANAGEMENT SURVEYING SPECIFICATION BUILDING REGULATIONS CONTROLS

STS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURA GINEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATIN

oject Title Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension

All details referenced in call outs supercede general arrangement or larger depiction

It is the responsibility of the Contractor to manage the Health and Safety

aspects of the project or nominate and agree a "Principle Designer".

ndicative in shape, size and location and are subject to a manufacturers and/or |

ruction reality & constraints tolerance of ± 300 mm in any direction or distance.

NOTES: Do not scale this drawing. All dimensions to be checked on site prior to

 \ll

 Δ

S 田

0

2

 \square

0

 \boldsymbol{Z}

0

ISTRUC⁻

CON

2 0

 \geq

Drawing Title Proposed U Value Calcultions

Drawn by RKC NTS 13.04.22 Checked by: Designed by: Approved by: RKC File Ref.: X:\201554-BREGS\(GA\60U\)
- T1-241205152522

Drawing No. 201554-A-601

24:12:05:15:25:29

Address: 54 Cokeham Road, Lancing, BN15 0AG Project : 2024 54 Cokeham, 54 Cokeham Road truction Type: Walls > Cavity Wall - Full Fill Insulation External Finish 100.0 0.6200 10mm low emissivity cavity 90.0 0.0210 100.0 0.5700 0.1754 0.2200 0.0591 alue = 0.19 W/m².K (combined method : 0.192 W/m².K, upper limit : 5.215m²K/W, lower limit : 5.215m²K/W, dUf : 0.0020) Client : Robert Cooper, Rapid Keystone Construction Consultancy Ltd Date: 16 November 2024 Address : 54 Cokeham Road, Lancing, BN15 0AG Project : 2024 54 Cokeham, 54 Cokeham Road enstruction Type : Ceilings > Insulation between Tiling including batten space Loft space 150.0 0.0220 6.8182 Insulation between joists Timber with joist spacing 12.5mm Gyproc Wallboard Inside surface resistance -value = 0.15 W/m².K (combined method : 0.148 W/m².K, upper limit : 7.548m²K/W, lower limit : 6.541m²K/W) Air Gap Corrections: Delta Ug = 0.0057 W/m2.K

Lady Lane Industrial Hadleigh, Ipswich, Suffolk IP7 6BA Client : Robert Cooper, Rapid Keystone Construction Consultancy Ltd Date: 16 November 2024 Address : 54 Cokeham Road, Lancing, BN15 0AG Project : 2024 54 Cokeham, 54 Cokeham Road nstruction Type: Walls > Timber Frame Wall > Insulation between and inside the studs > Conve Drained and vented cavity between battens Breather membrane Cementitious board 0.0220 4.5455 0.8500 Timber stud depth (mm) 25 x 47mm service void fixing batter 25mm service void air space 12.5mm Gyproc Wallboard Inside surface resistance U-value = 0.20 W/m².K (combined method : 0.196 W/m².K. upper limit : 5.572m²K/W. lower limit : 4.650m²K/W) Mechanical Fasteners : N/A Air Gap Corrections : N/A

Celotex products should not be used in the external walls of buildings over 11 metres in height. Recent changes to Building Regulations mean that only nor

Client : Robert Cooper, Rapid Keystone Construction Consultancy Ltd Date: 17 November 2024 Address: 54 Cokeham Road, Lancing, BN15 0AG Project : 2024 54 Cokeham, 54 Cokeham Road struction Type : Ground Floors > Solid - Insulation over slab P/A Ratio (Exposed internal perimeter divided by Polythene, 500 gauge separating layer 0.0220 4.5455 DPM - Polythene 1200 gauge Concrete oversite Sand Blinded Hardcore Mechanical Fasteners : N/A Air Gap Corrections : N/A

Client : Robert Cooper, Rapid Keystone Construction Consultancy Ltd Date: 16 November 2024 Address : 54 Cokeham Road, Lancing, BN15 0A Project : 2024 54 Cokeham, 54 Cokeham Road ruction Type: Pitched Roofs > Ventilated - Insulation Between & Under Rafters > Convent Tiling including batten space Sarking Felt Well Ventilated Cavity - minimum 50mm 0.0220 4.5455 0.8820 nsulation between rafters
 0.1300
 0.7692
 0.1180

 0.0220
 2.7273
 Fimber rafter spacing Insulation below rafters, taped joints as VCL 12.5mm Gyproc Wallboard side surface resistance Mechanical Fasteners : N/A Air Gap Corrections : Delta Ug = 0.0036 W/m².K

Client : Robert Cooper, Rapid Keystone Construction Consultancy Lt Date: 16 November 2024 Address: 54 Cokeham Road, Lancing, BN15 0A0 Project : 2024 54 Cokeham, 54 Cokeham Road ruction Type : Ground Floors > Solid - Insulation over slab P/A Ratio (Exposed internal perimeter divided by Polythene, 500 gauge separating layer 0.0220 3.1818 DPM - Polythene 1200 gauge Concrete oversite Sand Blinded Hardcore

Mechanical Fasteners : N/A

Air Gap Corrections : N/A

Client : Robert Cooper, Rapid Keystone Construction Consultancy Ltd Date: 16 November 202 Address : 54 Cokeham Road, Lancing, BN15 0AG Project : 2024 54 Cokeham, 54 Cokeham Road ruction Type : Flat Roofs > Cold Deck - Insulation Between & Below Joists > Convention Roofing membranes or coverings Insulation between joists Timber with joist spacing Insulation below joists, taped joints as VCL Inside surface resistance Mechanical Fasteners : N/A Air Gap Corrections : Delta Ug = 0.0073 W/m².K

SUBSTRUCTURE

Refer to the Structural Engineers design and details.

\sim D.P.C.

Horizontal dpc's to be min. 150mm above adjacent surface level to be 500 microns black polythene (2000g) to BS 6515, 1984. Dpc's to be provided horizontally (cill) and vertically (jambs) to all openings in external walls.

MASONARY IN GENERAL

If used, clay bricks throughout to be manufactured in accordance with BS 3921 Concrete blocks throughout to be solid and manufactured in accordance with BS 6073 Parts 1 & 2 and designated by the manufacturer as suitable for their intended location. Blockwork may be lightweight aggregate, 7n or aerated concrete provided that the specified structural, thermal and acoustic requirements are met. Alternative block densities to those specified may be acceptable subject to the proposed construction being supported by British Board of Agrement (BBA) Certification. All masonry construction to be built in accordance with BS 5628 Part 3 mortar shall be of the mix proportions necessary to achieve adequate strength and durability.

EXTERNAL WALLS / ROOF Timber Roof Construction - Form timber roof with 150 x 50 mm. joists, noggins, studs, head and sole plate. Studs to be at max. 400 c/c and covered externally with 12mm thick exterior quality ply (WBP) or OSB. Timber frame to be insulated with 100mm PIR insulation between studs and an additional layer of 50mm PIR insulation backed plasterboard to internal face. Seal junctions at floor and ceiling with mastic. Provide vertical tiling on 38 x 19mm tanalised horizontal battens and vertical battens on breather felt membrane fixed to external face of WBP/OSB. Lead soakers to be provided at junction of roof and dormer cheeks.

NON LOAD BEARING PARTITIONS

100mm x 50mm timber stud partitions at max 400mm centres. Studwork to have 12.5mm soundbloc lining to both sides taped and filled joints. Heavy fixtures should be made to the timber studs or independent framing installed prior to construction. All stud walls to • be fully filled with Rockwool insulation or similar approved.

Horizontal DPC below all ground floor partitions. Where plasterboard forms a junction with external walls and around openings, the edges are to be sealed with a continuous bead of sealant.

ightharpoonup STAIRS

All staircases to be timber and to meet the requirements of Approved O Document K1 Section 1. Min. 2000mm headroom, measured vertically above pitch line, to be maintained over all stairs. Rise and goings to be as noted on drawings all subject to checking site dimensions. Width of staircase as noted on floor plans. Vertical balusters at max.100mm centres where applicable or to provide a max space between so as to prevent a 100mm sphere from passing. Handrails to stairs and landings to be fixed to balusters 900mm vertically above pitch-line. Handrail to landings to be fixed 900mm above finished floor level. Handrail to balconies to be fixed 1100mm above finished floor level

CAVITY BARRIERS

 \circ

STRU

CON

 Δ

F0

NOT

— Cavity barriers to all cavity walls in accordance with Building Regulations Part B Document B3.

CAVITY TRAYS AND FLASHINGS

Code 4 lead flashings with min. 150mm upstand to be provided where roofs abut walls. Cavity trays to be linked to flashings in all cases and stepped in the case of a stepped flashing. Suitable cavity tray or flashing over all openings. Valleys to be lined with Code 5 ead.

FIRST FLOOR CONSTRUCTION

Unless otherwise stated on drawings all floors are to be constructed using graded timber joists. It is the Contractors duty to ensure all spans to be subject to checking by the Specialist Designers. Joist sizes, spacing and trimming to be in accordance with the drawings. Floors to be finished with 22mm weather deck or equivalent flooring grade moisture resistant T & G Type C chipboard / OSB to BS 5669. Lateral restraint to wall to comprise 30mm x 5mm galvanised mild steel straps with in-line noggins (38mm x 3/4 depth of joist) at maximum 2000m centres, unless shown otherwise on drawings and carried over minimum 3 No. joists. Noggins to be provided between joists supported on hangers off blockwork or structure in accordance with requirements. Ceiling to be finished with 15mm plasterboard to provide 10kg/m2, (soundblock).

Trimming to be provided where necessary to allow for SVP's and staircase opening all in accordance with joist layout drawings. Ceilings to be 15mm Masterboard to be taped and jointed. Provide fully filled Rockwool or similar approved insulation between floor joists and to fill all voids. Partitions parallel to the floor span but not located immediately over joists to be supported on full depth counter noggins between joists.

SOIL AND VENT PIPES AND BOXING

SVP's to be in 100mm diameter UPVC (unless noted otherwise on drawings) to BS 5572. Outlet to terminate min. 900mm above any opening into the building within 3m of outlet. Soil pipes to be encased in boxing constructed to achieve min. mass of 15kg/m2 formed from 38 x 38mm SW framing or similar faced with 2 layers 12.5mm plasterboard, joints staggered. Provisions to be made for access to SVP at floor levels. SVP's to be surrounded with min 25mm thick unfaced mineral wool throughout their length.

LINTELS

Lintels to be provided over all structural openings in accordance with drawings and structural Engineers details where deemed applicable. Lintels to be timber frame as part of roof construction. Cavity tray/damp proof protection must be provided over all external openings. Adequate end bearings of 150mm min. must be provided (any reduction must be to satisfaction of Structural Engineer) and lintel to be firmly fixed. Adequate fire resistance should be followed. Cold bridge paths should be prevented and adequate insulation measures incorporated.

PITCHED ROOF

Clay roof tiles as elevations to match existing. Installation to be in accordance with BS 5534 and BS 8000 on treated 38mm x 25mm SW battens (or size as specified by tile manufacturer) on Tyvek Supro breather membrane installed in strict accordance with manufacturers details for non-ventilated warm roofs, on rafters at pitches as indicated on drawings and max. 400mm c/c to BS 5268 Part 3. Rafters to be fully braced with 100mm x 25mm SW bracing, twice nailed to each rafter with 3.35mm (10 gauge) x 75mm long galvanised round wire nails, in accordance with roof design. Lateral restraint to be provided at rafter and ceiling tie level with 30mm x 5mm galvanised m.s. anchor straps fixed at each gable and wall as indicated on roof layout drawings.

Anchor straps to be spaced at max. 1200 centres and to be min. 1000mm long, turned down min. 100mm into wall cavity and screw fixed to masonry with 3 No. screws, one positioned inside 150mm of bottom end of strap. Wallplates to be 50mm x 100mm sw. anchored by 30mm x 5mm galvanised m.s. straps at max. 1200mm centres. Rafter and ceiling joist sizes to all roofs to be in accordance with Structural Engineer's designs. Ceilings to be finished with 12.5mm plasterboard 8kg/m2 taped and filled joints.

Skeilings to be insulated with 100mm PIR insulation between studs and an additional layer of 50mm PIR insulation backed plasterboard to internal face to achieve u-value 0.18w/m²k.

Insulation to dormers to include a single layer of 100mm PIR insulation between studs and an additional layer of 50mm PIR insulation backed plasterboard to internal face of studs to achieve u-value 0.18w/m²k. Dormer roof to be insulated as the main flat roof.

All penetrations through the roof are to be flashed as specialist manufacturers details.

NB: All information based on supplied third party survey information. NB: All levels are approximate and are subject to further site investigation All discrepancies to be reported to RKCC immediately upon discovery. I prior to construction. All discrepancies to be reported to RKCC immediately

FLAT ROOF

Warm flat roof construction to be 150x50mm joists at max. 400 c/c and covered externally with 19mm thick exterior quality WBP/OSB on min 25mm firrings to provide min fall of 1:80. Roofing felt membrane fixed to external face of WBP/OSB in accordance with manufacturers details and specification. Timber joists to be insulated with 150mm PIR insulation between and an additional layer of 50mm PIR insulation backed plasterboard to internal face. Seal junctions with mastic. Lead soakers to be provided at junction of roof and dormer cheeks.

RAINWATER GOODS

UPVC 100mm dia. rainwater gutters to be provided to roofs and discharging to existing down pipes provided at locations shown on plans and connected directly to storm water drainage system to the satisfaction of the Local Authority and in accordance with Approved Document H.

SANITARY GOODS

All waste fittings to have 75mm deep seal traps and separate connections to SVP's and to be installed in accordance with BS 5572. Wastes to wash hand basins to be 50mm diameter for runs up to 4m Baths and showers to have 50mm diameter for runs up to 4m length. Any branch pipes which exceed 4m, supply and fit an anti-siphon trap. Where necessary, pipes and hot water storage vessels are to be thermally insulated to comply with Approved Document L1, Section

SPACE AND WATER HEATING

Heating system to consist of radiators heated by existing relocated Gas boiler and in compliance with Approved Document L1. Hot water storage to be provided from thermal store unit located in linen cupboard (refer to drawings for specific locations) with 60mm insulation thickness min. Primary pipe work to be insulated in accordance with Approved Document L1 - generally in unheated areas and for the first meter run of pipe work from the thermal store unit.

FLUES

Boiler flue outlets to be provided with guard. Position of balanced flue to be not less than 300mm from any opening and in accordance with Approved Document J1. UPVC gutters within 850mm of flue outlet to be protected by min. 750mm long aluminium heat shield. Cavity wall insulation material to be neatly cut back to clear boiler flue by min. 25mm. The heating contractor is to ensure flue terminal is correctly fitted to ridge terminal/balanced flue as applicable, with clearance as specified by the gas company.

WINDOWS AND GLAZING

All windows to be doubled or triple glazed. All windows and glazed external doors to attain a max "U" value of 1.8W/m²K. Window style to be in accordance with elevations and schedules. Mastic sealant to be provided around perimeter of all openings. Where applicable obscured glazing to be provided to utility room, front door, bathroom, ensuite, and cloakroom windows. Glazing in entrance doors and sidelights within zone between finished floor level and 1500mm above (800mm in any internal glazed partitions) must be either one of the following:

- a. Toughened or laminated and break safely to BS 6206
- b. Robust i.e. 8mm annealed glass in panes not exceeding 1.1m in both height and width
- c. 6mm annealed glass in small panes i.e. max. width 250mm and area 0.5m2, all in accordance with Building Regulations Approved Document 1991 Part N1.

All opening lights (and doors) to be fitted with effective draught strips. Refer also to VENTILATION section in this specification.

FIRE RESISTANT DOORS

Fire doors to be provided as specified at locations defined in Schedules and contained within frames incorporating appropriate intumescent strips.

VENTILATION

In accordance with Approved document or as agreed by Building Control Officer.

All new bathrooms to have mechanical ventilation capable of extracting at a minimum rate of 15litres/sec

TIMBER

All external timber to be pressure impregnated with preservative prior to delivery to site In accordance with Approved Document or as agreed by Building Control Officer. Structural timber to be BS 5268: Part 2.

FIRE RESISTANCE

All steelwork to be encased or coated with intumescent paint to provide min ½ hour fire protection or as noted on drawings. Where recessed light fittings are used then an appropriate shroud by a specialist manufacturer should be used or contained in boxing from 12.5mm plasterboard on s.w framing to achieve min $\frac{1}{2}$ hour fire protection.

ELECTRICAL INSTALLATION

All new electrical work is to be designed, installed, inspected and tested in accordance with BS 7671:2001 or an equivalent standard These installation works are to be undertaken by a person registered with an electrical self certification scheme, or alternatively by a suitably qualified person, with a certificate of compliance produced by that person to Building Control upon completion of works.

Electrical layouts shown on working drawings are schematic only refer to specialist wiring layout drawings. Electrical installation to comply with I.E.E. Regulations and all relevant Codes of Practice. A number of light fittings within the dwelling should be suitable to take lamps with a luminous efficiency greater than 40 lumens per circuit-watt.

SMOKE ALARMS

Automatic smoke detection and alarm system in accordance with BS 5839 to be provided with a suitable number of mains operated, self contained smoke alarms to BS 5446: Part 1, fixed to ceiling at appropriate locations shown on drawings with at least one detector/alarm per floor, within 7m of doors to kitchens and living rooms and within 3m of bedroom doors. Alarms should be located min. 300mm from any wall or light fittings. Alarms should be permanently wired to a separately fused circuit at the distribution board and may operate at a lower voltage via a mains transformer. Mains units with secondary power supply are acceptable. For ease of maintenance smoke alarms should not be fixed over staircases

DRAINAGE

Work to be in accordance with BS 8301 and engineering drawings and Approved Document H or as agreed by Building Control Officer.

THERMAL BRIDGING AND AIR LEAKAGE

The individual air tightening measures will depend on the form of constructions and level of workmanship but the objective is to a form definable, continuous air leakage barrier around dwelling. Ways of preventing air leakage should then be considered at every penetration of this barrier.

- a. Joints between structural components e.g. wall to floors
- b. Joints around components and opening within walls.
- c. Services penetrations -plumbing, electrical and ventilation.

GENERAL

- a. Close any vertical ducts at top and bottom (e.g. boxing in to
- b. Seal any service penetrations.
- c. Select the appropriate sealant or gap filler for the size of the gap and degree of movement anticipated.
- d. Use joist hangers to support floor joists.
- e. Seal under skirting board and/or wall to floor joint intersection where dry lining is used and/or on suspended floors.

GENERAL NOTE

ALL MATERIALS AND COMPONENTS MUST BE SUITABLE FOR THEIR INTENDED PURPOSE AND LOCATION AND MUST BE MANUFACTURED AND INSTALLED IN ACCORDANCE WITH ALL RELEVANT, CURRENT BRITISH STANDARDS AND CODES OF PRACTICE AND MANUFACTURER'S SPECIFICATION OR AS AGREED BY THE BUILDING CONTROL OFFICER

ANY REFERENCE TO AN APPROVED DOCUMENT IN THIS SPECIFICATION RELATES TO THE RELEVANT APPROVED DOCUMENT OF THE BUILDING REGULATIONS

CHARACTERS LEGEND

- denotes centre line (typically when dimensioned)
- denotes centres spacing
- denotes diameter

is the responsibility of the Contractor to manage the Health and Safety aspects of the project or nominate and agree a "Principle Designer".

NOTES: Do not scale this drawing. All dimensions to be checked on site prior to encement or manufacture. PLANNING dwgs: All elements or entities shown are dicative in shape, size and location and are subject to a manufacturers and/or ction reality & constraints tolerance of ± 300 mm in any direction or distance.

DRA

THIS

FROM

BUILD

NOT

0

CONSTRUCTION

FOR

NOT

BUI


NOT

|

0

 \bigcirc

 \bigcirc



WWW.RKCCLTD.CO.UK 07985585488

TS QUANTITY SURVEYING CIVIL ENGINEERING SITE MANAGEMENT STRUCTURA NEERING ENVIRONMENTAL ENGINEERING SETTING OUT CDM ESTIMATIN

FOR ISSUED ENDER

Emma Day 54 Cokeham Road Sompting

> Roof Extension and Enlargement of Rebuild of Existing Conservatory, Lean-to Conservatory and Kitchen Extension

Drawing Title Proposed Building Regulation Notes

Drawn by 1:1@A1, 1:2@A3 13.04.22 Designed by: Checked by: Approved by:

 $File\ Ref.: \ ^{X\setminus 201554-BREGS\setminus GA\setminus 900\setminus}_{201554-A-900.DWG} \ -\ ^{T1-241205152607}$ 24:12:05:15:26:08 Drawing No.

201554-A-900



CONSULTING CIVIL & STRUCTURAL ENGINEERS


Heversham House 18-22 Boundary Road Hove East Sussex BN3 4EF Email: hove@dhk.co.uk


Structural Calculations


For

54 Cokeham Road, Sompting.

Date: June 2021 Project No: 59298








ROOF PLAN Scale 1:50 @ A3

Jub Title 54 C	OKEH	IAM ROA	54 COKEHAM ROAD, SOMPTING.	PTING.		ltem	ROOF PLAN.	
Designed by	AT	Date JUNE 2021	2021	Checked by	20	Job No. = 59298	Sheet 0.3	Rev.



350x250x15 BASE
PLATE FULLY WELDED
TO COLUMN AND
DRILLED FOR 4 No. M16
RESIN ANCHORS WITH
MINIMUM EMBEDMENT OF
150mm


350

TYPICAL BASE PLATE DETAIL Scole 1:20

DIXON HURST


Scale 1:20 @ A4

b litte 54 COKEH	54 COKEHAM ROAD, SOMPTING.	TING.	Item SECTIONS	SNO	
signed by AT	Date JUNE 2021	Checked by	Job No. 59298	Sheet 04	Rev.




SECTION 2-2 Scale 1:20 @ A4

Job Title 54	COKEH	AM ROAD, SON	IPTING.		Item		SEC	TIONS.	
Designed by	AT	JUNE 2021	Checked by	Ø	Job No.	59298	Sheel	05	Rev.




TYPICAL POST DETAIL Scale 1:20 @ A4



TYPICAL CONNECTION **DETAIL**

Scale 1:20 @ A4

Job Title 54	COKE	HAM ROAD, SOM	IPTING.		Item	TYPICAL DE	TAILS.
Designed by	AT	JUNE 2021	Checked by	18	Job No. 59298	Sheet O6	Rev.



SECTION 3-3
Scale 1:20 @ A4

Job Title 54	COKEH	AM ROAD, SOM	PTING.		llem		SE	CTIONS.		
Designed by	AT	JUNE 2021	Checked by	B	Job No.	59298	Sheet	07	Rev.	

o Tit		15	Ll M-	A	10	oA D	, «			F1								em				ı											
esign			PIP		_	ate	, 3	OP-	CP I	12		neck	ed b	ру		2						5 + C	_	neet					Re	ev.			
	1					グ UI	٦٤	2	.1							R	5	12	29	8				Ď	8								
_	LI	M	EL		p	ES	15	N		L	1																						
		_														_	Ш					_											
_	S	PA	N	=	4	.4	n			_			_									<u>_</u>						-			_		_
	1 -																																
_	LO	AU	IN	5	٥		-					124	-					-									_				-		_
_	<u> </u>	4.						D	,		-	[100]		,	n.	71	_	-	1	to.		,			_		_	-			H		_
	1-6	AT		RD	06			2	L			0.	75	^	14	7/	2	11	lan.	9	nv,	1/2						-					_
_	DA	D.E.	5	ζ,	Ü,			D	-			6.		Мы		11	_		E	0	и	1/2											
	_	-	_	5.	-			P	_			0.			m/m											\vdash							-
	50							1.						-	100																		
	10	TA	L	D	NF	a-c	50	RE	5		l) D	L	=	4	.6	и	/														Г		
						ro													19	6 ×	1.	8	=	6.	8	Nu,	100						
	VE	D	=	6-	В	×	4.	41	2	3	15	.0	Н	N																			
	Mo	D	=	6.	8	х	4:	42/	8	=	11	.5	h	N				Le	=	5,	0											Ш	
_	85	=	11	36	D	=	12	. 2	H	_																							
			_			. ur		_	0	a	n		14														_						_
	احدا	20	24	2.05	× (L4 × 10	7	~	8	9	δ	6	ب ^{بر}																				_
		,	- 1	200	^ 0	KIU	U 									_		-															
	tro	V I	DF		2	03	K	10	2 1	B	23		и	h =	21	. 5	NN	m			In	= 2	10	0,	_4			ζ,	=	2.	0	p	
				~		UTT	OM	P	_4T	E					0~													8	=	5.	2	p-2	
													_52																				
	PA	05	To	NE		DE	SI	ψIJ																									
	AR	EΑ		1	EQ	υı	LE	D	=	3,	5 x	75	00	0/	l _e	Sx	3.	5	=	10	00	0	n	_2									
							_										_																
4																	H							_		\vdash				_	-		_
-									_																۳	\vdash		-					_
	-							_								-								-							-		
-			-	-					-				_											-		\vdash		-					-
																										\vdash							



ob Ti 54	C		LE1-	IAM			CAC	, 5	S 0 µ	AP T							T				De	<u> </u>	_											
Design A	ned b	ру				ate UN	E 2	21			Ch	neck	ed b	У	1	}	Jo S	9 N	o. 298	8			Sh	eet 69					Rev	·.				_
	TR	IM	ME	R	l t	ND	ER		Po	ST																								
	-	-							-																							T		
+	5	24			1	1.6	_			Н																\exists				1	-	+	-	-
+		14	7	=			-	_						_	-												-			-		+	-	-
					_																									4		_		L
	Lt	AD	111	u																														
					AD	F	11 10			00	37	=	26	- 8	(April		D.	0	-3															
	-				110		100	2					2	. 0	Dille?		-																	Ť
+	-			Y 4				-		\vdash	_	_		-					_	_			_		-		-1	H	H	+		-		Ī
_	R	Ŋ	=	11	9,5	N	ر		p	0.5	7.	3	- 0	ļ																	_	4		L
	M	=	5.	85	ы	N/A																												
T	Un		=	3	8.	7	11.0	. /	-																									
	-	_					4.	-/		7																			\vdash			\dashv	\dashv	
+	-			~	_	c	6	,				_	_	7	- A		3		۹.	-					_				-	-		+	\dashv	
	Z	2	=	٥.	8	S K	10	11	. 2	5 x	7.	5	=	6	24	X1	0	-	١,								-			_		_		
	I.	4	=	5	x	W	×	<u>_</u> 4		=	3	1 %	1	X)	0	-	- 4																	
		7	20	2 1	72	POX	7 -	1																				П						Ī
+			30	7.4	14	POK	51										H																	Ī
+-	_		_			_			-		_		_		H	_		-						-			-	-		-	-	-	_	
	50	50									_						Ш													_				
					Z	5	10	Ox	20	0	16	=	66	7	x 10	3	m	3																
00					٢	=	10	o x	20	3	In	=	66	.7	KID	6		_4																
1	T				*		, · ·	-	20	0	12				110															1				Ī
+	-	_			-				-			-					-		-			H				\dashv		-		+	-+	-	-	_
-	_												_				_		_					_	_			_		4	_	-	_	
																									Щ									
	Pa	0	VI	DE	:	2	Nº		50	x	20	0	. Y	10	24		T	IM	BE	15														
												_	_				-			_	-													Ī
+-																		Т	==												T			
+						-											H											H	-	+	-	-		
+	1		_			-			-		_	_					-				_				_	-		H	-	-	-	+	4	
																												Ш						
																														T				
																																		ĺ
+	-		_			-			-		-	_					-	-							-	-			-	+	-	-		Ī
+			-			-					_																			-	-			
-																							4								_			
																																		ĺ
1	t		_																=															
+	1		-						-						H		H				H							H		+	-	-	-	
+	-					-			-									ļ	_									-	-	-	-	_		
															\perp																			
																												П						
+						1												\vdash										П		+	+	+		
-	1			-		-	-		-		-	_	_	H		_				-	-		_						-	-	-	-	_	
									_												Ш							Ш	\sqcup	_	_	_		
																																		ĺ



CONSULTING CIVIL & STRUCTURAL ENGINEERS

	C		-EHI	Apr	_		, 5	OM	PT	IN	_						_	EAI		Dt	SI	GN	_					_	_				
_	ed b	ру				ite V⊷	E 1	21			C	neck	ed b	у				1 2	o. 98				Sh	neet 10					Re	:V.			
	BE	AM		DE	S١	c	2		B	1																							
	5	PΑ	N	=	5.	4~											_																_
	10	4.0	IN					_								_	-				-				-				_				
-	20	PU	110	(tr	5							(יבוו	1				-								-								
	F	しの	on					a	し			0.	3	k	6.	3/	2	=	1,	58	н	2/	~										
	Ė		-					L	L) ×	S	x	6.	3/	2	=	a.	7	И	11									T		
	ß	EΑ	m	S	·w			D	L			٥٠		ho																			
														,																			
		TA	1						ED		U	DL.	=	6.	68	h	w/	m			_		1 -										
H	10	TA	1	F	HC	TO	RΕ	עו	U	UL	45	1.5	4×		48	+	1 -	6	×	4.	7_	=	10	• 3	ы	W/	prop.						
	٧e	D		10	.3	×	5.	9/	2	=	3	0 -	4	1-	n																		
	ME	D	=	10	.3	Х	5.	42	18	=	4	4.	8	h	ba			1	e.	=	6.	0~											
	85	=	2/	2.5	0	=	23	.6	h	_							-		_														
	G.		- 1					_	,		П																						
	IA		_		_	_	L+	_	=	2	1	7	9	6	m4																		
		3	84	x	20	Sĸ	8x1	07																						_			
-	PR	DV	מו	E	•	15	7.	х	15	2	U	L	3	7		N	b =	5	1.2	h.,		T.	, <u>-</u>	22	10	2.3			١,	-=	16.	4	-
					Ė		Ė		Ė	=	Ě	=	Ě	Ė				. 0				•				-			01			1	
																								M	Aχ		ЬL	LO	WA	BL	E		
	1.							. Ii																LI	_	_	Lo	AD		DE	PLÉ	CT	101
															L									~	17	20							
	1	(C) 4	_			_														_													
	H										-																						
																														Г			
										2																							
																	-																
H																_	_									-							
						1			1	I										1			1	1			I			1			



b Tit 54		٥٥)	KE	HAI	M	R	OAT	,	501	мρ	TI	NO					lte I	EAI	1	D	ES	1 4							-				
esign A		У				ite (UN		21			Ch	eck	ed b	У	-	&	Job 5	9 Z). 9 8				Sh	eet					Re	V.			
	BE	AM		D	:5	15	2		B	2																							
	,	0.4			2	. 2																										+	
	2	PA	13	=	٥	. 4	~			Н																							
	L	DA	ומ	N	G																												
						ΑD		FR	ОМ		P	os	7	=	П	. D	n	2		@	6	.7	,		U	LS							
	B	EA	M		5-	Q			D						:																-		
			\dashv	1	: •	Ö	MM			-															-					-	+	+	
-	,	0.7	\downarrow					W	= 0	. 4	2 h	1/2				Ra	=	8-	60	+	0.	6	7	=	9.	26		ИР					
					-	,	-	,	-		L		-			RL	=	34	0	ŀ	N	9/											
1	Ru												4	Ь		M	9	6.	5	0	-	0	-1	=	6.	4	0	MN	ind.				
_	,												<u>_</u>	,				De	=	3	* S	~											
					_		3.	20																				-				-	
	V	DL	=	6	.4	0	×	8	1	3.	22		=	5	. 0	н	-/	<u>_</u>	υ	LS													
									-				=	3,	37	Ph.	10		S														
	50	=	4/	25	0	=	12	- 8	pa .	-																							
	T.	2 =	5	×	w	xL	4		=	1	7	3	Cit	4																			
		3	84	x Z	05	x &	×I	ot		Ė																							
-	PA	OU	10	E	1	1.5	2	X	8	9	υ	B	16	-						ran	,		Ine	至	83	4	وموعا			ξ=	1.	33	
		_														©.	3.	5														-	
	PA	PS	TO	N	E		DE	Sı	G	1																							
	A	RE	A	_	RE	al	11	E	D	=	3.	2	×	52	491	143	97	16) /	10	5	× 3	. 3	=	6	14	-7	75	1	_2			
						-						H	-																				
																150																	
					-									-							-	-						-		-			
-			_		-				-			-	\vdash	-																			
														_																			
							-	-		-							-				-							-		-			
+				-			-			-				-			-				-			1	-			-					
\vdash																					1												
		-																															



CONSULTING CIVIL & STRUCTURAL ENGINEERS

signe	ed b	у	- C		Da	te				V.()	Ch	eck	ed b	у	- (Ž,	lot	o No). . 9 8			14	Sh	eet					Re	 ≥∨.			
A ₁		_				3U+	ع د	2	1			_			_		3	1 4	. 10		T =		_	12		_	(U)						_
			_		_										_																	\rightarrow	
	B€	Α	M		D	ES	1 G	·N		B	3																					_	_
																																_	
	5	PA	N	=	2	.6	~																										
	L	OA	ומ	N	G	5																											
												140	12																				
	F	Lo	OR.					Þ	L				S	×	4	1/2	11	1	.0	14	N/	н											
								L	L			I)	5	ж		2		3.			w/	_											
	BE	AM		5.	w			D	L			0.	4	144	In																		
	To	TA	L		U	NF	AC	10	RE	D		UP	L	=	4	.4	h	~/	μη.														
	Ta	TA	L		FA	CT	OR	E	D				=	10	4	X	1.	4	+	Įį.	6	×	3	į.	6.	8	ы	~/	m-1				
		12			LO			FI	OM				w			ST	UD	=	12	. 0	K 2	.5)	x	3.	2/				0	0	Je	5-	
	1																								ő								
				l. ((_			4.) HI	د			R	a_	=	8	. 8	4	+	100	5	4	E	10	. 4		J						
1		6		-8		n	1						R		=	8	. 3	н	N														
											T		И		21	. q	-	8	.7	=	7	. 2	11	NO									
	L			_							11		1.	23	Re	-	3	.0															
1				_	2	-6	_				K				, ,			Ť												Г			
	U	DL	=	7.			8	11	2	=	2	. 5	6	w/		- 10	LS																_
	Ť				-		0	-		=	5	٠٦		W/			LS																
	П										_		Ť	~/																			
	5_	11	2/	25)	11	10	-4																									
	or		-/	23)		10	·ψ		~																							
	Т		5	×	LA	J	, 4			=	1	5	q	_	, 4																		_
	114	-	30	T v	20	5	(107			_	5	1	6	j~ '		_									-							
-			مر	* *	20	- X	Q.K	10				-										-											
\vdash	Pn	M	10	E	3	15	2	<u>.</u>	15	2 0	· C.	22			Mb		17					т		83	(30	4		(1	10		
+	-	OV	10	کا	-	=		_	13	- 0		23						2 1	(No			At	=	0.3	TC	M .	_	- 9	1=	-	rO	~~	
	H								-		-				<u>e</u>	3,	OM.									_		H					
	On		-				D			, 1																							
-	<u>(14 </u>	n?	10	Ŋ	ß_		DF.	51	T	7	-				-	-		-	_											\vdash		\dashv	
\vdash	Λ	0 ~	Λ		0 -		, ^	F.D.	_	2		10		_	1-	-	,	-		6	93	(L		2						\vdash			_
	Н	RE	μ		RE	ΘÜ	IR	ED	=	5.	58	10	40	0 /	3.	5×	1,	5	=	6	13	4	m	m									
	6	A		C4		_			~		,		_	-				-										_		-			_
-	-	00	N	DA	11	O	N		ME	51	G	N		-					H	-	-	-			-								_
	Λ	00				_	-						_	_		100		-							-					H			_
	Н	PΡ	LL	EO		L	DA	D	=	7	• 5	4-	7.	4	=	15	.4	h	N											-			_
	1 -						_												-	-						_				-			_
	μS	50	М	ED		ي	BY	=	10	0	h.	In																					
	٨								_				,								_									-			_
	/A]	LE	A		Le	0	ונ	Ke	U	=	15,	4	/10	0	4	0 -	16	n	2				_	_				_					_
																					1												



BEAM S PA L DI F LS F LA	A TO CEAM	N	= RO. (1)	2.6 35 S	I I I I I I I I I I I I I I I I I I I		13 13 10 10 10 10 10 10 10 10 10 10 10 10 10		0. 1. 0. 0. 1.	83 75 0 4	X X X X X	3. 3. 2. w/	4/4/5	2 2 2 = X	= = = 2	2 4	4 45 28 m	h h	6	m m		7	14	13	.2	Į-n	N/o			
S PI L DI F Le F LA	A TO CEAM	N	= RO. (1)	2.66 5 :5 :5 W W W W W W W W W W W W W W W W W W W	S II		D OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3,	7		13	.2	j.a	w/n			
S PI L DI F Le F LA	A TO CEAM	N	= RO. (1)	2.66 5 :5 :5 W W W W W W W W W W W W W W W W W W W	S II		D OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3,	7		13	. 2	Į-i	w/n			
E LO	A TO	>1111 >K T E 100 4	Rocce Si	A LUW FACOR	I I I I I I I I I I I I I I I I I I I		OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3.	7	11	13	. 2	j-1	w/n			
E LO	A TO	>1111 >K T E 100 4	Rocce Si	A LUW FACOR	I I I I I I I I I I I I I I I I I I I		OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3,	7	1	13	. 2	<u>j</u> -1	who			
Ex S F S F Poli	A TO	DR T E 10 D D D D D D D D D D D D D D D D D D	1200 CL NO.	A LUW FACOR	I I I I I I I I I I I I I I I I I I I		OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3.	7	11	13	.2	<u>j</u> a	w/o			
Ex S F S F Poli	A TO	DR T E 10 D D D D D D D D D D D D D D D D D D	1200 CL NO.	A LUW FACOR	I I I I I I I I I I I I I I I I I I I		OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3,	7		13	. 2	Įn	W/n			
ExTOTI POINT	A TO	T = 100 m	5.	FA C			OM		0. 1. 0. 0. 1.	5 5 83 75 0 4	X X X X X	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3.	7	14	13	. 2	Ņ	w/s			
ExTOTI POINT	A TO	T = 100 m	5.	FA C			OM		1. 0. 0. 1.	5 83 75 0 4	X X X X ===	3. 3. 2. w/,	2/ 4/ 4/ 5	2 2 2 = X	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3.	7	11	13	. 2	Į-l	w/o			
Ex. S FO	XT U	E 10	5.	FA C	II II CT C) L) L) L Fe	OM		0. 0. 1. 0.	83 75 0 4	X X X 14	3. 2. w/,	4/4/5	2 2 = X VO	= = = 2	2.1.1.5	4 45 28 m	h h	~/	m m	3 .	7	11	13	.2	ĵu ju	w/2			
Ex. S FO	XT U	E 10	5.	FA C	I I CT C	- L) L) L - FE	OM		0.	75 0 4	X X 118	3. 2. w/.	4/ 5. A ST	2 = X	= = 2 2 5.	1. 1 5	45 28 11	h V	~ /	m M	3	7	11	13	. 2	М	w/n			
Ex. S FO	XT U	E 10	5.	FA C	I I CT C	- L) L) L - FE	OM		0.	75 0 4	X X 118	3. 2. w/.	4/ 5. A ST	2 = X	5.	2 4	28 h	l.	6	×	3.	7	11	13	. 2	М	w/n			
S FOTO POIL	TA L	D 1	5.	FA C	I I	L	OM		0.	0 4 L	K	2- w/, 1.	5 4 5T	×	5.	2 4	h +	U/on	6	×	3.	7	72	13	. 2	М	w/n			
S FOTO POIL	TA L	D 1	5.	FA C	CT C	L REFE	OM		0.	4	14	1:	4 5T	×	5.	2 4	+	l#.	6		3	7	1	13	. 2	М	w/s			
TOTAL POINT	TA L	1 T	.6 1	FA C	CT C	re Fe	OM		UD	L	=	le L	4 5T	S	=	4					3.	7		13	. 2	М	w/n			
TOTAL POINT	TA L	- T	.6 1	FA C	CT C	re Fe	OM		UD	L	=	le L	4 5T	S	=	4					3.	7	11	13	. 2	ы	w/n			
POIL	IN 1	1.	.6	, OA	HD .	Fe	OM		_			L	ST	S	=	4					3.	7	=	13	. 2	ы	w/n			
POIL	IN 1	1.	.6	, OA	HD .	Fe	OM		_			L	ST	UD	=	4					J.	/	<u> </u>	1 2	- 6	Ņ	W/n			
4 Ra		1.	.6	,	ļ				EX	n E	K N P						.0	@	1.	6.		\dashv								
4Ra	4 =	_	_			4-0	PERS.					Ro	=	17	.2				H 10						. 1					+
4Ra	4=	_	_		/~ \							Ra	=	17	.2							\dashv				-1				
4Ra	6 =	= 1 3	3 - 1	Hay	/a \\		-	-				Ro	=	117	. 7					H		\dashv								
1				-				1	1 2		+-	-		11	, 4	+	1-	54	Ξ	18	.7	H	J							
1		_					_	ļ	Ų.			_	=	19	.6	ы	IJ													
Upi			- 1	-					BA	0		M	=					13	. 3	=	13	. 5	h	24						
U DI		_		2.	6-				100			1051	1	=	3	٠٥	-													
Upi																														
)L =	=)	13.	5 ,	x 8	1/1	=	16	-0	и	10/10		UL	S			29													
								10	.7	и	w/m	_	SL																	
8=	= 1	11.	25		= 1	0 -4																								
	1																													
Inx F-		5	×	<i>,</i>	K L	4	=	2	99	1	4					П						\Box								
					Sal			-	Ħ		-																			
	90	- 1	7 2		OKI																									
PRO	27/	מו	E	: 1	5 2	×	2 9	110	1/			MI	= 1	7			\vdash		Т	- 0	3.4-	6				(.		1 8	q_	
7 100	V .		Ü				u l	QD	10	=	-	_	3.	-	- F	INM			44	= 8	34	Cm'				SL	-	PS	7.7	27
	+				+							(a)	2 %	0-		-							-							
nac	0,1-	اء ح				+	-				-	H																		
PAD	731	101	りき		E S	15	Ŋ	-															Н							
W A -			_	_			-	1	e	3 -	1		-		-		F	-	10		15.	_	2-	_						
ARE	EA		LE 1	メレ	11 R	E D	=	2 *	2	X [9 (00	1	3.	5 x	11	2	=	13	0	67	, bi	m ²		_					
	-			-	_	+	-				_						-		_		_	_					H			
	4				_																		Ц							
	_					-																								



4			H phas	[LOP	D,	Sc	MP	TIN	ے در							B	EAV	u	De	51	50											
signe A	ed b				Da	ate いん					Ch		ed b					o No			*			eet					Re	÷∨.			
	BE	Ajų		Œ	51	GN		ß	5																								
							_		_	_																							
	5	DA	N	=	4.	8	n																										
	Lo	AD	IN	cr	5																												
												hu	/m2																				
	FI	0	OR					D	L				5	X		21	2	1	0.	8	HN	10											
								1	L			١,	3	x	3.	2/					MA												
	F	LAT		Ro	ÞΕ			12	L			6.	85	уŁ	8.	0/	2	11	3.	4	Ин												
						a T		L	L			0 .	75	X	8.	0/	2	1.1	3.	0	MN	Im											
	Ē	XT	ER	NA	L			D				٦.	0	Х	2.	5	=	2:	5	Hay,	1-												
	B€	AM		5 - 1	J			D	L			0.	4		1																		
					UN	FA	6	TO	RE	D		UD				2.							_										
	To	T	AL		FA	CT	OR	ED		D	L	=	Lx	4	X	7.	1	+].	6	X	5.	4	=	18	. 6	L	12/	m				
	Ye	D	=	19.	6 ×	4.	8/	2	=	44	.6	h	Ŋ																				
							7																										
	Me	D	=	18	-6	×4	-8	18	=	5	3.	6	HN	M				Le	-	5.	2	m											
	91	=	4	25	0	=	19	.2	n	^							_							_									
	_		_			_	4					_			_	-			_					_	-								
	195	1	5	K	W	x	2	-	Ξ	1	19	5	C	^*					_										_				_
-		3	84	x 2	05	λ {	XIO	-		-		_	_		_	_	_	-	_					-	-	_	-	-	-				
-	20	2.1		_		1					-		_				6	,					r	-	55	12-0		0				3.3	
-	PK	OV	IV	6	:	2	54	X	14	6	UB	3	7_	H) •	O þ	אט			Jan	-	37	40	Com	4		9	=	Del	
-						_						_			0	5.	5~																
-	DA.	חר	Ta	11.		D:	()			1	-					-	-	-	_						-		_	-					
- #	H	105	To	NE		DE	31	4	N	7	-								_						-								_
	n	RE	Δ		DE	00	10	ED		=	3.	5	у.	120	6	0/	7	۲.	1 -	<	-	2	97	34		2							
	r.	r~C	1-1		140	O-V	116	EV			٠.		^	4	00	0/	2,	-	, ,	5	Ħ	^	1.1	24	m	m						\Box	
			-																														
	24	05	TO	NE		DE	51	Us		2																							
T T			, 0	~		150	1	- 6		-																							
	AR	FA		Ra	20	12	E D		3	-5	x	44	60	0+	27	40	13	.5	κl	.5	=	3	15	60	n	_~ 2							
	- 1			100	, ,				Ť	Í				Ė	71		,																



4	C ned b	01	(EH	AM	П	201 ate	AD,	5	0 &	107	11	cr	- d l-			-		_				GN	_	eet	_				Rev				_
_	rea t	,	,		٥			2	1		Cr	neck	ea c		- —	& —	5	92	o. 48	3				eet S					Rev				
	B	EH	M		DE	SI	c	N		B	6																						
																																	Ī
	5	PA	7	=	2.	9 ,	,																										Ī
																																	Ī
	10	AD	12	4	s																												
													Nn,	62																			
П	F	10	o L						D	L						3.	2/	2_	=].	4	и	1/-					П					
			-						L	L						3.			7				1/_										Ī
	FL	AT		KO	06				D	L	П		0.	5	Х	8-		2	-				1/2					П					
									L	L			j.		х			2	=	6.			1/-										
	Ex	アド	RN	AL					D	L			1.	_	-	2.	_	=	_	_		-/m											
	-	AM		5.					D	L			_	_	-	~/,												П					-
		POR		s.					-	L				5		2/																	
					U	NE	AC	TO				UD	-	-		14																	1
			L		Ac					UD	L					8			6	×	7.	2	=	21	. 0	и	12/1	П					
							Ť																		П								-
	VE	n	=	21	. 0	×	1.	9	12	=	3	0.	5	H	N													П			T		
													_																				-
	ME	D	=	21	. 0	х	2.	q 2	18	=	2	2.)	h	N.				Le	=	3.	3-			П								Ī
																			52									П					
	5-	-	L/	36	0	_	8	9.1	~																								
																												П		T	İ		-
	I,c		5	×	w	K	14			=	7	7	7		~ 4													П					
					20						Ħ	-					-														Ħ		Ī
																									П								-
	PR	Dν	10	E	:	2	03	×	10	2	IJ	В	2	3			ML	= 2	9.	1 4				In	-	21	00	. 4		8.	- 3.	0_	
	PR	тн	8	25	ľ	OF	To	u	P	LA	TE		~				(A)	3.	5_	- 1	477			- 1000	Ť	21	00	cm.		0.			-
																									П					\top			_
	PA	25	TO	N/G		G	ES) G		4																				\top	\vdash		-
		_	_	-6				- 4	\sim		-																						-
	A	RE	p		LE	6.10	10	E	D	=	3.	5	к	30	50	0/	1.	5 =	2.	5	=	2	02	34	1								
	,,,	100	, .	П	20	~ u	116								Ť		-	2.4	5,5				ر	J ()	-		-						-
																																	-
	PA	DS.	50	NE	-	۵	55	10			2																						-
_		_				_	50	.0	2		~	-													П								=
	AR	EA		LE	QU	116	ED	=	3	2.	×	(3	05	00	+	22.	00	/1	. 5	×	3.	ς	1	2	1 2	00		~~					
		-				- 4-2			Ť	_		-					-	/ !		1		_	Ė	7		-							
																				_													
																									-				===	=			-
	П																																
	H																														1		_
																				-												-	
																	-			-					-				-	_	-		



t			NAP	1	_		. S	01	1P T	וטו							_	EAI	_	D	ES	161	_						<u> </u>				
sign A 1	ed b	ру				ite ろい	νĒ	2	1		Ch	neck	ed b	У	K	3		91		8				eet 16					Re	ev.			2.
	B	EΑ	M		DE	Ś١	4	u		B	7										Ш												
	S	PA	u	=	3	.2	jes																										
	10	AD	12	6	S																												
											1400	12																					
	C	1/1	ME	Y			0	L			2	0	x	0.	53/	2	X	4	.0	11	13	. 2	ы	N/	_								
	BE	AM	S	·W			D	-					MUZ																				
H																																	
	W	L	=	1.	4	x	¥3	. 6	=	19	-0	120	υ/	n	1																		
	W					х				0			31			1							ų.										
П											Ħ		1					R.a	=	0	- 9	4	+-	0.	74	,	17	7	AJ.				
-											1	11 =	19	NA	/_			T.C.		-	Ť	-		lad.			-	-					
				lat.	1 =	0.	(-	1			Г	1	Ť					RL	=	9.	4	h		П									
	_			w.		0,	, n	~~		-	1	-	+					0	É	1.00	Ė	и	-	Н					T				_
-	JR.	- 1				((4		H		_			4	PL	H			Į,	_	9.4	x1×	. 25	-	l.	11	-	2	- 1	3	He	1		
-	, 1-0				2	-7.					7	0.	5 . /					2-	5	11.4		- 35	1	-	10		- 6	Ė		Lie	-		
					_	- 1		Н						-			-		-		_									-			_
			_				. 2			,,			_			_	_	L	=	3	. 5	_		-				-	-	-			
	ŲD	1	= 2	- 1	3 x	8/	L			66		-																					_
								=	1-	11	h	·Im	5	1.5						-	-		-	_		-	_	-	-		-		_
_	,				_				-			-				_										_	_		-				
	0 T	=	1/	36	0	=	8.	4~	-								-							-	H	_			H	-			
																						-	-	_		-			-		-		
	In					ХL				8	3.	12	~ *	_	_	_	_		_				-	_					-	⊢			
		3	84	X 2	05	x (8×1	0,1		_						_							-	-					-	-			
																							-				_	_	-	-			
										_												_	_	-				-	-	-	_		
	PR	OV	ID	E	;	15	2	× 8	9	υß	16					=	15	-1	M	-			Im	=	83	4	mt		8	~	1,	0	1
_															0	3.	5,													_	_		
																												_	-	_			
	PA	05	Го	N	Ξ		DE	51	G	W														_							_		
	A	RE	Α	(LE	au	12	ED	=	3	. 5	×	17	00	11	15	x 3	.5	=	11	30	n	~2					L					
									Г																								
								П																									
															П																		



Title																	lte																
4 (0	Ke	= t	1A	М	R	DA	0,	50	MP	1	N (X			ž.	(.01	-01	U L)	DE											
signed Δ	by T				Da		ΝĒ	2	1		Cł	neck	ed b	у		8	Jol 5	0 No). - 9	ĸ				neet 17					Re	V.			
	İ	T	Т	-													_		_					14									
Po	5-	T		DE	SI	C	N																										
			Ĭ																														
H	=	- 7	2.	5	'n																												
U	L	S	4	R	EA	CT	10	N	S																		4		_	_		_	
Α.	-	-	4	_	=27	_		in	2)		_	_	10	L.		_				V	. \	_	_		4			Н	_	\dashv	4	+	
Ax									3)								4	25.	7	RB	1/	=	7	4.	4	HU				\dashv	-	+	
									.3				.0	<	100	•	D/	_	2	9	_												_
PIU	PI,	EA	2(12	1		110		^ 3	. 1	Į A	L.	2	X Z	. 3	/•	-	5	, D	14	13 1900											
TO	11	1 L		:	12	0	x	8	0	R	14.5	5	.0																				
le	×	2	=	1.	2	Х	2.	5	=	3-	0	n																					
Re	y	,	=	2.	0	×	2.	5	=	5.	0	~																					
									_					_		_	Ц													\perp			
							ריקניו						2																	_			_
VY.	Ey	=	1	7.	1	И	NA			- 9	Pey	-	14	4	14	ψ¥							_										
Ve	H	+	u			h.4			74	9	_	2	_	_	0	_		0	7		4	_		1	17						-		_
Pe			2			Pcy			14		+	7.1	+		1 6		O	- 0	/_		-L	0.		U	10			Н			=		
100		1	23			1						3.11																					
PR	0	V	11	D	E	÷	1	2	0	X	8	0	R	HS	5	- 0	-																
	_	+	_					_			_														_		_				_		
F	DI	<u> </u>	١	DA	1	10	2	_	D	ES	16	2	_					_				L				_			_				-
Δ	00	2 1	-	ξD		_	=0	Sr I	CE		1	DΑ	D	=	4	a	q		IJ		Н												
	1.6	L	4 (50		2	CIC	4 1	Ce		L	UP			4	1.6	-	L	N)														_
A	55	U	M	EC	is.	Gr	BP	=	10	0	L	w/	m ²																				
AR	E	A		a	EO	UI	26	0	=	49	. 4	11	00	=	0	. 5	m²																
181		*			8				_																			H					
		+																	_											-		+	
		-	+				H											-												\dashv		-	
		+	+										-																				
			\dashv																											\exists	Ħ		



CONSULTING CIVIL & STRUCTURAL ENGINEERS

	C						40	, 5	501	иρ						,		RAI			S	&		50		5						
-	ed b	у		- 0	Da 5		E	21			C	eck	ed b	У	,	18	Jol 5	0 No 9 Z	o. . 9 §	}				eet 18				F	Rev.			
																									Ĭ							
	0.0	ET	ΕR	<																												
-	KP		EIC	٦	_	-				H		_				_		_				\neg		7	_		+	+	_			_
-		0.					_		_	-	_	_	_			_		-2.0	-		-	-		-	-		+	+		-		
	٤	ra	N	=		65	~	(0	PL	AU.			Au	6	E	=	3	80				_		-	-		-	+	-			
				=	2.	15	^	(6	1 Tc	н)															_		_	1				
	Lo	A	ΡI	2	CFS																											
		L					lat	12																								
	_	L				0	PA														H								+			
-	L	_		0.	15		100/	an.													-	_				-	+	+	+-	-		
		_				_	_												_		-		_	-	=	-	+	+	+-		H	
	F	RO	M		TR	AD	Α	T	AB	LE	5															_	4	+	-	-		
	PL	01	ID	E	:	5	0	X	10	0	10	16		2.A	FT	E	RS		0	4	00	c,	1									
-																																
	F	Δ	T		0 _	-		50	10	T.																						
-	_	-	-	-	40	DF	-	20	12	12												-			-	-	+	+	+	Н		
-		_			_	_	_					_	_		_		-	-	_					-	-	-	+	+	+			
	51	A	N	=	3	. 2.	м													_					-	_	4	+	-			_
																										_	_	4		Ш		
	Lo	DA	13	16	5																											
	D	L		0.	65	И	0/	, 2																								
	ι			0.	75	,		_2																			T					
					7.5	j-	N.	~																		_	+	+	1			
	м		-	-			_	-		-		_	_							_		-		-	H	-	+	+	+-	Н	Н	
			М		TR	AD	A		TA	RI	ET	5			AT					_				-		-	-	+	-			_
	PR.	OV	l D	E	*	5	0	X	15	0	10	24)	FL	AT		RO	OF		50	15	15	_				-	-	4			
	1	D	OK		50	15	rs																									
- 2	Ť		- 10		70	-																										
		D A	2	_	2	2			H	-																			+			
_	9	() A	2	=	٥	. 2	,	-	-			_		-				-			-				-	-		+	-	-		-
						_	_							Ш												-			-	-		
	LO		1	N																-	_					_		1	-			
	D	L	ii		.2		MA	1_2																								
	l	Ł			. 5			12																								
	E 1	1	M		10	AD	n		T	ΑB	1=	<																				
									_		24	-	Y	.00	P		e i	, -	,			_				+		1	1			
-	I K	UV	10	E) as	2	D X	15	O	10	-4		1-1	-0(111		01	51	5			-					-	+		-		
																											-	-				
													_			_											_		_			
				H											1													Ť				
		-	_	-			-	-			-				-	-	-			-				-	H	-	-	+	+	-		
											_				1		-			-	-					_	-	100	+	-		
				11	10		III.	411		ICI.					1		MI.			1					- 11			111		1	1	



	tle	ملم		N 1- 1		0 -	.A.		s -								lte				۸.		l.e										
	ر ned ا		ŧΗ	_	Da	ite				my	_		ed b	y	<u> </u>	0	-		_		CH	150		neet		_		_	Re	·V.			_
3,6	AT					5Un	リビ	2	. 1					_	0	\$			48					19									
	50	15		C	15	۷	n	U	ND	EL		YLΑ	FT	ER	2																	_	
L	5	PA	Ŋ	=	3	•	m																										_
								_									_								-	_		_	_				_
_	120	AD	١N	5	5	_	-		_							_	_									_			_	-			
_	-					10				IAM				-	-	_	1						-	-		-							_
_	F	LO	01			D	L		-	1.	5	x		4	11 11	0.	6		-/->						_	_			_				
-	15	1 /	In			D	L				25	_	0.	4.	=	0.			1/2											H			-
-	100	ا ا	12	UP		L.	L	- 50	-		25	_	0.	4	=	0.		11/40	_			1											
	Po	IN	-		LO		10	@	ı	-6	-	-		HA		-			-	10		, řii											
	10	IN	I		LO	r		0		0	-	_F (5)	-	PTK																			
-	i i		1	. 6			1		,,,								Lu	=	0.	9	5	+	0.	0	7	+	0.	41	=	1,	5	HN	
	_	الزا	=	0.	5 MA	lin	1		[A]	2=	0.	2 4	iefa				Rb	=	1.	08	I4	نز											
	Г	Ť					7						7				M	=	1.	3	9	his	m						124				
	la			1.6	^		X						1	Nb			1+6					ļγ			H								
						3	. f	n					_																				
	UD	4	=	1.7	9·x	8	12	2	=	1.	16	и	N/	اسم																			
																_																	
	Z	1=	1.	34	rio	11	. 2	5	Χ	7.	5	=	14	8	χì	03	m	h3												_			_
	_		_												_															-			
_	-ve						4		=	13	,4	X	10	0		197.4	ų													_			
	4		381	A I	080	Ox3	×L															-			-		_						
_	-		-			2	11		1.0	0		2	_	2															H	-	-		
_	Z	c	50	X	15	0	16	=	18	8 ×	סו		r	~°										,									
	T	_	6	K	15	V3	112	_	10	-1		0		4																			
	1		3	D K	13		112	-	14	-1	ΧI		-	^								\vdash									<u></u>		
														,																			
	PM	ov	ID	E	:	5	Э×	1	50		CZ	a)	F	LO	OF		く	018	TS	()	12	40	0%	6		ji,							
	1.65	T		F								É		Ť	Ė	1									=								
																														-			
					_									_						_			_							_		_	
		_	-		_		_		-										_	_			-				_			_			
	-	-	-		-		-													-	-	-					-	-					
		\vdash	-											-			_		-	-	-	-					-	-		-	_		
		-					-		-						-			-	-	-	-	-	-	-			-	-	-	-		-	_
		-	-	-		-			-			H			-					-								H	-	-			
	-	-					-		-			-		-	<u> </u>					_	-	-		-	-	-	-	-	-		-	-	

o Title	(0)		HA	м	_	_	D,	٤	OM	PTI	_		J L.			_		EA		Ī.	DES	10	_	eet				_	Re					_
esigne 1	ed by				Da ර		ع د	2	1		Ch	еске	ed by	y 	N.	5		No 9 2						19					110	v. = 1	- 1	-		
																												_		_	_	-		
	n	D	4	E	В	EA	M		RB	7																			_		_	4		_
																												_				_		
	5	PA	2	=	6.	2,																										-		
					1																											_	_	
	LO	AD	IN	U	5																									Ш	_	-		
														Иν,																		4		
	FL	$\overline{}$		Ļ	11	rci	EC	2		D	L			٥.	85	X	6-	5/	2	=	2.	8									-	-		
	R	_	_								L_		_		75			5/	2	=	2.	4	Hu	/n								+		-
	13	EA	М		5.	w				D	L			0.	4	no	/m														-	-	-	
																			_			_										+	-	
							CT					VD			5					_									_	\vdash		-	_	-
	To	TΑ	L	F	AC	TO	ÆΕ	D		ay	L	=	9	4	К	3.	2	+	1.	6	Х	2.	4	=	8.	5	И	0/2	1		-	-		-
	A .					_	,	2	,										-					-			-							+
	VE	D	=	8.	3	X	6.	4	12	-	15	e 1	MN																			\exists		-
-	,	_					6 -	221	U		0.5				A		6	. 5					-	_								+	_	-
-	Me	D	5	8.	3	X.	6 -	2/	٥	=	40	-0	444		120	=	U	. 2	_			-	-	-			-	-				=		
-	(ne			_	_			_																				Ì
-	5 T	=	L/	25	0	=	73	•0	~~																								П	
	Im						4		-	2	10	2			-4			_			-													t
-	- KA	20	5	X	W	X L	-	-			10	_		6	-			-			_		Г											İ
-	-	38	Q-X	20	ÞΧ	97	10					-																		П				Ì
+	Pa	_	VI I	D	-		15	2	×	15	2	110	3	7			Kal.	=	47	.0	Maria				1-	=	22	10	6	+		8=	0.	1
	-		y !	13		Ė	Ė	-						Ė	Ť		6	ľ	0~		-10											-	4	
	\vdash						1										100	12.14																
+	Po	ST		r	1=	51	G	N																										
	1	3 (-0	Ė																										
	Н	=	2	. 4	m																													
	_		IN	-		1	13	- 6	K	80	7	1	2	K	1.	4	=	34	1	ķ	N													
			LI				RE						1-	2				1																
																									L									
	Je	1	Ь	=	2	4																				L		L						
	Ec		To				0/	6.	8	=	8	15	3		J	la,		0	. 4	8	7													
																												_		_				_
	AL	10	WI	13	LE		ST	RE	SS	=	6.	487	×	0	8	X	6.	8	=	2	. 6	5			-	-	-			-				_
																				_		-	-		-	-	-			+				-
	PR	01	ILD	E	7	10	007	13	0	10	16	T	10	B	K		Po	51					-			-	-	-	-	-				
																				-	-	-	-	-	-	-	-	-	-	+	-			_
									1		-					-			-	-		-	-	-		+	-		-	+				-
						-		-	-			_	-	-	-	\vdash	-			-		-	+	-	+	+	+			+-				-
	1_	_	_	-	-	_		-	-	-			-	-	-	-	-	-	-	-	-		+	+	-	+	+	-		-	-	H	-	-
-		-	-	-	-	-	-		-	-		-		-	-	-	-	-	-	\vdash	-	1	+	+	+	+	+	-	-	-	-			-
- 1		1												1																4				_

Dixon Hurst Ltd

Consulting Civil & Structural Engineers

Heversham House, 18-22 Boundary Road

Hove, East Sussex BN3 4EF Tel: (01273) 421444 449 Joh

Job Ref

Sheet : / 21


Made by


Date

: 22 June 2021 / Ver. 2015.05

Checked : /

Approved :





Welds grd E 35 Plates Grade 43 Beam 152x152 UC 37 [S275]

End-Plate 182 x 175 x 20 mm (5 kg) 4 No. M24 Grade 8.8 Bolts in 26 mm holes

RB1 SPLICE Beam to Beam End-Plated Connection to BS 5950 Loading Case 001 Basic Data

User Defined Applied Forces at End-plate Interface

Resultant Forces M, Fv, F

40.0 kNm, 26.0 kN, 0.0 kN

Grade 8.8 Bolts

Load directions

Top of Joint in Tension, Rafter moving Down.

Design to

BS 5950-1: 2000 and the SCI Green Book: SCI-P-207/95

Basic Dimensions

Beam-152x152UC37 [28]

D=161.8, B=154.4, T=11.5, t=8.0, r=7.6, py=275

Bolts 24 mm Ø in 26 mm holes

Plates Grade 43, Welds E 35

Rafter Capacities Mc, Fvc, Fc 84.9 kN.m, 213.6 kN, 1295.5 kN

Mc = 84.9 kN.m OK

Summary of Results (Unity Ratios)

Moment Capacity 40.8 kNm	(for 1 rows of bolts) (Modified Applied Moment Mm=40.0 kNm)	0.98	OK
Shear Capacity		0.07	OK
Flange Welds	0.84	0.84	OK
Web Welds	0.94, 0.38	0.94	OK

Dixon Hurst LtdConsulting Civil & Structural Engineers, Heversham House, 18-22 Boundary Road, Hove, East Sussex BN3 4EF


Ref.:, / , Date: 22/06/2021

6

MasterKey Joints -

12449

RB1 SPLICE



End-Plate 182 x 175 x 20 mm (5 kg) 4 No. M24 Grade 8.8 Bolts in 26 mm holes

Welds grd E 35 Plates Grade 43 Beam 152x152 UC 37 [S275]

₩ 6w



	ned l		-0 11	Art	_	Roy ate	AU	, ,	ОМ	PII		neck	ed F)V	A	9		IM i			νς,	316	_	neet					Re	· ·			_
	AT					5Ur	νE	2	1			IECK	eu c	, y		& 	5	92	98				JI	23					110	v.			
	TI	MB	ER		LIN	TE	L	D	ES	16	N																						
												Ī																					
	5	PA	7	=	2	.5	_																										
	Ť																																
-	10	10.0		,															_			H			_	\dashv						\dashv	
+-	60	AD	IN	G	>				_	_									_		-	_				\dashv		-	-		-	-	_
-														/m2			-	_	_			<u>_</u>					_						
-	F	LA	T		Ro	oF			D	L			0-	80	X	3	. 3	12	-	13	3	2	H									_	
									L	L			0.	75	×	3 .	3	12	=	1.5	2	4	И	4	_								
	T	OT	AL		UP	L	=	2	. 56	Н	2/	الميرا																					
	Ve	n	=	2.	5 6	X	2	, 5	12	=	3	2	n	N																			
T	1												, ·	П									10					П					
+	Ne		=	2.	56	¥	2.	52	18	=	2.	0	h	NA								\vdash									\dashv		
	I'VE		-	-		^	~	-	-	Ė	_ '	U.	- rl	N								-										\dashv	
\vdash	-			_			. 6	1.		-	7	5	_	2	2 /		_3		7.		-											-	
	Zie	2	=	Z •	0	χl	0	/ 1	• 2	Эx	1.	5	=	4	14	X	0	n	3-		_	_						-				\dashv	
														,		_																\perp	_
	I	2	=	5	x W	x	L4			=	2	5 ×	10	6	~	4																	
		r .	38	4×	72	0.0	x 3	K	L																								
	50	50			Z	=	1	00	x	15	02	16	=	3	75	x1	3	,	2														
	Г									Ħ				Ť	, -	-						3							\neg				
0	\vdash	_			_	-	10		_	16	2	112	_	2	0	- A	5		4-													\dashv	
	\vdash		_	-	4	7	70	10	_	13	0	112	-	2	D	A I	U	H	۴,					-	_				\dashv			+	
-	\vdash		-													-	-								_				-			-	
-	-		_										_				_				_		_	_	_				_		_	_	
	_			Ш							Ц.		_									_											
	PR	OV	ID	E	•	2	N ₀		50	x	15	0	10	24		TI	MB	ER_	5														
				-																									_			+	_
H										H																							
-	-		_	-	_	-			_	-			_	-						_	_			-	-	\dashv						-	
	-				-			_				_	_	-						_				L.					_			_	
	1												_			_																	
																_																	
																					ľ												
H																																	
-	+																				-					-	\dashv	-				+	
-	-																										_		_				
-	-		_		_					-		_	-			-	-					-		_	-			H					
																						_											_
																																-	



CONSULTING CIVIL & STRUCTURAL ENGINEERS

ЬΤ																	lte	m															
	C		EH	MA			D,	\$	DM.	PTI	~	r					1	RIV	чи	ER	٤	HO	ck										
	ned I				Da S	ate Sun	E	2	1		Cl	neck	ed b	у	K	3	Jo 5	0 No	o. 98					neet 2 4					Re	V.			
								Ť	Ė								-							ri				П				Ī	
	1	Д	FT	E	1		Va	ID	1	KI	ш	ше	n																				
T	1			Ť	1		7.0	-			_																						
	S	PA	N	=	J.	4	5																							\Box		T	
	Lo	AD	ΙŃ	U	٤																												
	191	TC	HE	D		RO	OF			D				0.	85	K	3.	11	Z	7 ⁰	10	32	. }	w/	a-ri								
										L	L			0-	75	x	3.	1/	2	=	10	16	Н	~/	_								
	10	TA	L	U	DL	=	2 -	48	n	4	2																						
													_								L											_	
	Vē	D	=	2	.4	8	X	10	4/	2	=	1.	7	4	Н	J																	
	4.4		_	_				. 2)		_	1.						_								4				\dashv		-	
_	ME	р	=	2.	48	X	-	4	18	=	0-	61	h	א פו				_			<u> </u>					-				_		-	_
	-			/ .		. 6			_		2	_	0	0		3		3							_					\dashv		-	
	ZM	1=	0.	61	×Ι	U		. 2	5 x	5.	٥	=	٦	ZX	10		سر معر	Ĺ								-		H		\perp		-	
	T	, =	r				4	_	_	5	1		26	_	١.		-	_					-		_			_		\dashv		-	_
	100	=	5	× 6	N	OK	2 ×	,	_	3	* I	χı	0	Jan.	^ `		-				H				_			H		\dashv		+	
	+	5	84	ΧJ	80		3^	L															_			-						+	
-	50	50																-	-	,		-				-				-			
0					7	=	10	Οx	10	2	11	_	1.6	7.	10,3		3													-			
					T.	=	10	Ох	10	73	/12	-	8.	3 x	10	8	-	4							=								
							Ė										100													\exists		_	
																								П									
	PR	ov	ID	E	,	2	no.		50	x	10	0	10	16	T	100	BE	125		IA S	T	RI	MM	EL									
																									-								
										Ш																							
					_				-																							_	
	+		_			_								_	_																	-	
																		_							_								_
_																										\vdash		H				-	
_	-	-					-					_														-						+	
-	+												-																			-	_
	-											_							_														
	+									H								_				_			_	\vdash			_			-	
	+		H														-															-	
																										+						-	
						H		_			_							_				_				+						-	
-	-					-	-	_		-					-	-	-	_	_			_			_	\vdash	-	-		\rightarrow	-	-	_